

Édition 2024



Courbes de puissances

UE RESIDENTIELLES MULTISPLIT

Hisense

Official Partner

Aldes



2AMW35U4RGC - UE MULTI 2
POSTES 3,5 KW



2AMW42U4RGC - UE MULTI 2
POSTES 4,2 KW




2AMW52U4RXC - UE MULTI 2
POSTES 5,2 KW



3AMW72U4RJC - UE MULTI 3
POSTES 7,2 KW



3AMW52U4RJA - UE MULTI 3
POSTES 5,2 KW



4AMW81U4RAA - UE MULTI 4
POSTES 8,1 KW



4AMW105U4RAA - UE MULTI 4
POSTES 10,5 KW



5AMW125U4RTA - UE MULTI 5
POSTES 12,5 KW

2AMW35U4RGC - UE MULTI 2 POSTES 3,5 KW

4. CAPACITIES AND SELECTION DATA

12K

COMBINATION (%)		Cooling Operation PERFORMANCE DATA																																																					
		OUTDOOR DB (°C)																																																					
		IDDB (°C)	ID WB (°C)	-15				-7				0				10				15				21				25				27				30				35				40				45				50			
				Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT				
130%	21	18	2.66	1.53	0.58	220	2.66	1.53	0.58	246	2.66	1.53	0.58	272	2.95	1.70	0.58	289	2.95	1.70	0.58	323	4.49	2.59	0.58	684	4.30	2.47	0.58	719	4.13	2.38	0.58	752	3.97	2.29	0.58	787	3.75	2.16	0.58	838	3.44	1.98	0.58	890	3.18	1.83	0.58	923	2.64	1.52	0.58	959	
	21	20	2.79	1.27	0.46	260	2.79	1.27	0.46	286	2.79	1.27	0.46	312	3.10	1.41	0.46	329	3.10	1.41	0.46	363	4.72	2.15	0.46	716	4.52	2.06	0.46	753	4.34	1.98	0.46	788	4.18	1.90	0.46	824	3.94	1.80	0.46	878	3.62	1.65	0.46	932	3.35	1.53	0.46	968	2.78	1.27	0.46	1004	
	22	18	2.66	1.64	0.62	220	2.66	1.64	0.62	246	2.66	1.64	0.62	272	2.95	1.82	0.62	289	2.95	1.82	0.62	323	4.49	2.77	0.62	684	4.30	2.65	0.62	719	4.13	2.54	0.62	752	3.97	2.45	0.62	787	3.75	2.31	0.62	838	3.44	2.12	0.62	890	3.18	1.96	0.62	923	2.64	1.63	0.62	959	
	22	20	2.79	1.39	0.50	260	2.79	1.39	0.50	286	2.79	1.39	0.50	312	3.10	1.54	0.50	329	3.10	1.54	0.50	363	4.72	2.34	0.50	716	4.52	2.24	0.50	753	4.34	2.15	0.50	788	4.18	2.07	0.50	824	3.94	1.95	0.50	878	3.62	1.79	0.50	932	3.35	1.66	0.50	968	2.78	1.38	0.50	1004	
	22	22	2.96	1.11	0.38	299	2.96	1.11	0.38	325	2.96	1.11	0.38	351	3.29	1.24	0.38	368	3.29	1.24	0.38	402	5.00	1.88	0.38	748	4.79	1.80	0.38	787	4.60	1.73	0.38	823	4.43	1.66	0.38	861	4.18	1.57	0.38	917	3.83	1.44	0.38	974	3.55	1.33	0.38	1011	2.94	1.11	0.38	1049	

Remarks:
 Q: Total Cooling Capacity (Gross) kW
 SHC: Sensible Heat Capacity (Gross)
 SHF: Sensible Heat Factor
 IPT: Power Input (including the compressor, evap. fan motor & cond. fan motor) W
 DB: Dry Bulb Temperature
 WB: Wet Bulb Temperature

2AMW35U4RGC - UE MULTI 2 POSTES 3,5 KW

4. CAPACITIES AND SELECTION DATA

COMBINATION (%)		Cooling Operation PERFORMANCE DATA																																																				
		OUTDOOR DB (°C)																																																				
		IDDB (°C)	IDWB (°C)	-15				-7				0				10				15				21				25				27				30				35				40				45				50		
Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT											
90%	21	18	2.29	1.28	0.56	183	2.29	1.28	0.56	204	2.29	1.28	0.56	226	2.54	1.42	0.56	241	2.54	1.42	0.56	270	3.86	2.17	0.56	574	3.70	2.07	0.56	604	3.55	1.99	0.56	632	3.42	1.92	0.56	661	3.22	1.81	0.56	704	2.96	1.66	0.56	747	2.74	1.54	0.56	776	2.27	1.27	0.56	805
	21	20	2.40	1.06	0.44	223	2.40	1.06	0.44	244	2.40	1.06	0.44	266	2.67	1.18	0.44	281	2.67	1.18	0.44	310	4.06	1.79	0.44	607	3.89	1.71	0.44	638	3.74	1.65	0.44	668	3.59	1.58	0.44	698	3.39	1.49	0.44	744	3.11	1.37	0.44	790	2.88	1.27	0.44	820	2.39	1.05	0.44	851
	22	18	2.29	1.37	0.60	183	2.29	1.37	0.60	204	2.29	1.37	0.60	226	2.54	1.53	0.60	241	2.54	1.53	0.60	270	3.86	2.32	0.60	574	3.70	2.22	0.60	604	3.55	2.14	0.60	632	3.42	2.05	0.60	661	3.22	1.94	0.60	704	2.96	1.78	0.60	747	2.74	1.65	0.60	776	2.27	1.37	0.60	805

Remarks:
 Q: Total Cooling Capacity (Gross) kW
 SHC: Sensible Heat Capacity (Gross)
 SHF: Sensible Heat Factor
 IPT: Power Input(including the compressor, evap. fan motor & cond. fan motor) W
 DB: Dry Bulb Temperature
 WB: Wet Bulb Temperature

2AMW35U4RGC - UE MULTI 2 POSTES 3,5 KW

4. CAPACITIES AND SELECTION DATA

			Cooling Operation PERFORMANCE DATA																																																			
			OUTDOOR DB (°C)																																																			
COMBINATION (%)	IDDB (°C)	IDWB (°C)	-15				-7				0				10				15				21				25				27				30				35				40				45				50			
			Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT
80%	21	18	2.19	1.18	0.54	162	2.19	1.18	0.54	182	2.19	1.18	0.54	201	2.44	1.31	0.54	215	2.44	1.31	0.54	241	3.71	2.00	0.54	515	3.55	1.91	0.54	542	3.41	1.84	0.54	567	3.28	1.77	0.54	593	3.10	1.67	0.54	631	2.84	1.53	0.54	671	2.63	1.42	0.54	696	2.18	1.18	0.54	722

Remarks:
 Q: Total Cooling Capacity (Gross) kW
 SHC: Sensible Heat Capacity (Gross)
 SHF: Sensible Heat Factor
 IPT: Power Input(including the compressor, evap. fan motor & cond. fan motor) W
 DB: Dry Bulb Temperature
 WB: Wet Bulb Temperature

2AMW35U4RGC - UE MULTI 2 POSTES 3,5 KW

4. CAPACITIES AND SELECTION DATA

12K

HEATING PERFORMANCE DATA

COMBINATION (%)	INDOOR DB(°C)	OUTDOOR WB(°C)															
		-15		-10		-5		0		5		10		15		20	
		Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT
130%	15	5.06	1479	5.95	1524	6.61	1540	7.27	1571	7.90	1654	8.53	1737	8.96	1789	9.23	1824
	16	5.00	1491	5.88	1537	6.54	1552	7.18	1584	7.81	1667	8.43	1751	8.85	1803	9.12	1839
	17	4.94	1503	5.81	1549	6.46	1565	7.10	1597	7.71	1681	8.33	1765	8.75	1818	9.01	1854
	18	4.88	1515	5.74	1562	6.38	1577	7.01	1609	7.62	1694	8.23	1779	8.64	1832	8.90	1869
	19	4.82	1527	5.68	1574	6.31	1590	6.93	1622	7.53	1708	8.14	1793	8.54	1847	8.80	1884
	20	4.78	1539	5.62	1587	6.24	1603	6.86	1636	7.46	1722	8.05	1808	8.46	1862	8.71	1899
	21	4.72	1556	5.55	1604	6.17	1620	6.78	1654	7.37	1741	7.96	1828	8.36	1882	8.61	1920
	22	4.66	1573	5.49	1622	6.09	1638	6.70	1672	7.28	1760	7.86	1848	8.26	1903	8.50	1941
	23	4.61	1591	5.42	1640	6.02	1656	6.62	1690	7.19	1779	7.77	1868	8.16	1924	8.40	1963
	24	4.55	1608	5.35	1658	5.95	1675	6.54	1709	7.11	1799	7.67	1889	8.06	1945	8.30	1984
	25	4.50	1626	5.29	1676	5.88	1693	6.46	1727	7.02	1818	7.58	1909	7.96	1967	8.20	2006
	26	4.44	1644	5.23	1694	5.81	1712	6.38	1746	6.94	1838	7.49	1930	7.87	1988	8.10	2028
	27	4.39	1662	5.16	1713	5.74	1730	6.31	1766	6.85	1859	7.40	1952	7.77	2010	8.01	2050
28	4.34	1680	5.10	1732	5.67	1749	6.23	1785	6.77	1879	7.31	1973	7.68	2032	7.91	2073	
29	4.28	1698	5.04	1751	5.60	1769	6.15	1805	6.69	1900	7.23	1995	7.59	2055	7.81	2096	
30	4.23	1717	4.98	1770	5.53	1788	6.08	1825	6.61	1921	7.14	2017	7.50	2077	7.72	2119	
120%	15	4.91	1408	5.78	1452	6.42	1466	7.06	1496	7.67	1575	8.28	1654	8.70	1703	8.96	1738
	16	4.85	1420	5.71	1463	6.35	1478	6.97	1508	7.58	1588	8.19	1667	8.60	1717	8.85	1752
	17	4.80	1431	5.64	1475	6.27	1490	6.89	1521	7.49	1601	8.09	1681	8.49	1731	8.75	1766
	18	4.74	1443	5.58	1487	6.20	1502	6.81	1533	7.40	1614	7.99	1694	8.39	1745	8.64	1780
	19	4.68	1454	5.51	1499	6.12	1514	6.73	1545	7.31	1627	7.90	1708	8.29	1759	8.54	1794
	20	4.64	1466	5.46	1511	6.06	1526	6.66	1558	7.24	1640	7.82	1722	8.21	1773	8.46	1809
	21	4.58	1482	5.39	1528	5.99	1543	6.58	1575	7.15	1658	7.73	1741	8.11	1793	8.36	1829
	22	4.53	1498	5.33	1545	5.92	1560	6.50	1592	7.07	1676	7.63	1760	8.02	1812	8.26	1849
	23	4.47	1515	5.26	1562	5.85	1577	6.42	1610	6.98	1694	7.54	1779	7.92	1832	8.16	1869
	24	4.42	1531	5.20	1579	5.78	1595	6.35	1627	6.90	1713	7.45	1799	7.82	1853	8.06	1890
	25	4.37	1548	5.14	1596	5.71	1612	6.27	1645	6.82	1732	7.36	1818	7.73	1873	7.96	1910
	26	4.31	1565	5.07	1614	5.64	1630	6.20	1663	6.73	1751	7.27	1838	7.64	1894	7.87	1931
	27	4.26	1583	5.01	1632	5.57	1648	6.12	1682	6.65	1770	7.19	1859	7.55	1914	7.77	1953
28	4.21	1600	4.95	1649	5.50	1666	6.05	1700	6.57	1790	7.10	1879	7.45	1935	7.68	1974	
29	4.16	1618	4.89	1668	5.44	1684	5.98	1719	6.50	1809	7.01	1900	7.37	1957	7.59	1996	
30	4.11	1635	4.84	1686	5.37	1703	5.90	1738	6.42	1829	6.93	1921	7.28	1978	7.50	2018	
110%	15	4.77	1381	5.61	1423	6.23	1438	6.85	1467	7.45	1544	8.04	1621	8.44	1670	8.70	1703
	16	4.71	1392	5.54	1435	6.16	1449	6.77	1479	7.36	1557	7.95	1634	8.34	1684	8.60	1717
	17	4.66	1403	5.48	1446	6.09	1461	6.69	1491	7.27	1569	7.85	1648	8.25	1697	8.49	1731
	18	4.60	1414	5.41	1458	6.02	1473	6.61	1503	7.19	1582	7.76	1661	8.15	1711	8.39	1745
	19	4.55	1426	5.35	1470	5.94	1485	6.53	1515	7.10	1595	7.67	1674	8.05	1725	8.29	1759
	20	4.50	1437	5.30	1482	5.89	1497	6.47	1527	7.03	1607	7.59	1688	7.97	1738	8.21	1773
	21	4.45	1453	5.23	1498	5.81	1513	6.39	1544	6.95	1625	7.50	1706	7.88	1758	8.11	1793
	22	4.39	1469	5.17	1514	5.74	1530	6.31	1561	6.86	1643	7.41	1725	7.78	1777	8.02	1812
	23	4.34	1485	5.11	1531	5.68	1546	6.24	1578	6.78	1661	7.32	1744	7.69	1796	7.92	1832
	24	4.29	1501	5.05	1548	5.61	1564	6.16	1595	6.70	1679	7.23	1763	7.60	1816	7.82	1853
	25	4.24	1518	4.99	1565	5.54	1581	6.09	1613	6.62	1698	7.15	1783	7.50	1836	7.73	1873
	26	4.19	1535	4.93	1582	5.47	1598	6.02	1631	6.54	1717	7.06	1802	7.41	1856	7.64	1894
	27	4.14	1552	4.87	1600	5.41	1616	5.94	1649	6.46	1735	6.98	1822	7.33	1877	7.55	1914
28	4.09	1569	4.81	1617	5.34	1633	5.87	1667	6.38	1755	6.89	1842	7.24	1897	7.45	1935	
29	4.04	1586	4.75	1635	5.28	1651	5.80	1685	6.31	1774	6.81	1862	7.15	1918	7.37	1957	
30	3.99	1603	4.69	1653	5.22	1670	5.73	1704	6.23	1793	6.73	1883	7.07	1939	7.28	1978	

2AMW35U4RGC - UE MULTI 2 POSTES 3,5 KW

4. CAPACITIES AND SELECTION DATA

COMBINATION (%)	INDOOR DB(°C)	OUTDOOR WB(°C)															
		-15		-10		-5		0		5		10		15		20	
		Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT
100%	15	4.63	1340	5.45	1382	6.05	1396	6.65	1424	7.23	1499	7.81	1574	8.20	1621	8.44	1654
	16	4.58	1351	5.38	1393	5.98	1407	6.57	1436	7.14	1511	7.72	1587	8.10	1634	8.34	1667
	17	4.52	1362	5.32	1404	5.91	1418	6.49	1447	7.06	1524	7.62	1600	8.01	1648	8.25	1681
	18	4.47	1373	5.26	1416	5.84	1430	6.42	1459	6.98	1536	7.53	1613	7.91	1661	8.15	1694
	19	4.41	1384	5.19	1427	5.77	1441	6.34	1471	6.89	1548	7.44	1626	7.82	1674	8.05	1708
	20	4.37	1395	5.14	1438	5.71	1453	6.28	1483	6.83	1561	7.37	1639	7.74	1688	7.97	1722
	21	4.32	1411	5.08	1454	5.65	1469	6.20	1499	6.74	1578	7.28	1657	7.65	1706	7.88	1741
	22	4.27	1426	5.02	1470	5.58	1485	6.13	1515	6.66	1595	7.20	1675	7.55	1725	7.78	1760
	23	4.22	1442	4.96	1486	5.51	1501	6.06	1532	6.58	1613	7.11	1693	7.46	1744	7.69	1779
	24	4.17	1458	4.90	1503	5.44	1518	5.98	1549	6.50	1630	7.02	1712	7.37	1763	7.60	1799
	25	4.12	1474	4.84	1519	5.38	1535	5.91	1566	6.43	1648	6.94	1731	7.29	1783	7.50	1818
	26	4.07	1490	4.78	1536	5.31	1552	5.84	1583	6.35	1667	6.86	1750	7.20	1802	7.41	1838
	27	4.02	1506	4.73	1553	5.25	1569	5.77	1601	6.27	1685	6.77	1769	7.11	1822	7.33	1859
28	3.97	1523	4.67	1570	5.19	1586	5.70	1618	6.20	1703	6.69	1789	7.03	1842	7.24	1879	
29	3.92	1540	4.61	1587	5.13	1603	5.63	1636	6.12	1722	6.61	1808	6.94	1862	7.15	1900	
30	3.87	1557	4.56	1605	5.06	1621	5.56	1654	6.05	1741	6.53	1828	6.86	1883	7.07	1921	
90%	15	4.47	1316	5.26	1357	5.84	1371	6.42	1399	6.98	1472	7.54	1546	7.91	1592	8.15	1624
	16	4.42	1327	5.19	1368	5.77	1382	6.34	1410	6.89	1484	7.45	1558	7.82	1605	8.05	1637
	17	4.36	1338	5.13	1379	5.70	1393	6.27	1421	6.81	1496	7.36	1571	7.73	1618	7.96	1650
	18	4.31	1348	5.07	1390	5.64	1404	6.19	1433	6.73	1508	7.27	1584	7.63	1631	7.86	1664
	19	4.26	1359	5.01	1401	5.57	1415	6.12	1444	6.65	1520	7.18	1596	7.54	1644	7.77	1677
	20	4.22	1370	4.96	1413	5.51	1427	6.06	1456	6.59	1533	7.11	1609	7.47	1657	7.69	1691
	21	4.17	1385	4.90	1428	5.45	1443	5.99	1472	6.51	1549	7.03	1627	7.38	1676	7.60	1709
	22	4.12	1400	4.84	1444	5.38	1458	5.91	1488	6.43	1566	6.94	1645	7.29	1694	7.51	1728
	23	4.07	1416	4.79	1460	5.32	1474	5.84	1505	6.35	1584	6.86	1663	7.20	1713	7.42	1747
	24	4.02	1431	4.73	1476	5.25	1491	5.77	1521	6.28	1601	6.78	1681	7.12	1732	7.33	1766
	25	3.97	1447	4.67	1492	5.19	1507	5.70	1538	6.20	1619	6.70	1700	7.03	1751	7.24	1786
	26	3.92	1463	4.62	1508	5.13	1524	5.64	1555	6.13	1637	6.62	1718	6.95	1770	7.16	1805
	27	3.88	1479	4.56	1525	5.07	1540	5.57	1572	6.05	1655	6.54	1737	6.86	1789	7.07	1825
28	3.83	1495	4.51	1542	5.01	1557	5.50	1589	5.98	1673	6.46	1756	6.78	1809	6.98	1845	
29	3.78	1512	4.45	1559	4.95	1574	5.44	1607	5.91	1691	6.38	1776	6.70	1829	6.90	1866	
30	3.74	1529	4.40	1576	4.89	1592	5.37	1624	5.84	1710	6.30	1795	6.62	1849	6.82	1886	
80%	15	4.33	1303	5.10	1343	5.67	1357	6.23	1385	6.77	1458	7.31	1530	7.67	1576	7.90	1608
	16	4.28	1314	5.04	1354	5.60	1368	6.15	1396	6.69	1469	7.22	1543	7.58	1589	7.81	1621
	17	4.23	1324	4.98	1365	5.53	1379	6.08	1407	6.61	1481	7.14	1555	7.49	1602	7.72	1634
	18	4.18	1335	4.92	1376	5.47	1390	6.01	1418	6.53	1493	7.05	1568	7.40	1615	7.63	1647
	19	4.13	1346	4.86	1387	5.40	1401	5.94	1430	6.45	1505	6.97	1580	7.32	1628	7.54	1660
	20	4.09	1356	4.81	1398	5.35	1413	5.88	1441	6.39	1517	6.90	1593	7.24	1641	7.46	1674
	21	4.04	1371	4.76	1414	5.28	1428	5.81	1457	6.31	1534	6.82	1611	7.16	1659	7.37	1692
	22	3.99	1386	4.70	1429	5.22	1444	5.74	1473	6.24	1551	6.74	1628	7.07	1677	7.28	1711
	23	3.95	1402	4.64	1445	5.16	1460	5.67	1489	6.16	1568	6.65	1646	6.99	1696	7.20	1730
	24	3.90	1417	4.59	1461	5.10	1476	5.60	1506	6.09	1585	6.57	1664	6.90	1714	7.11	1749
	25	3.85	1433	4.53	1477	5.04	1492	5.53	1522	6.01	1603	6.50	1683	6.82	1733	7.02	1768
	26	3.81	1449	4.48	1493	4.97	1508	5.47	1539	5.94	1620	6.42	1701	6.74	1752	6.94	1787
	27	3.76	1464	4.42	1510	4.92	1525	5.40	1556	5.87	1638	6.34	1720	6.66	1771	6.86	1807
28	3.71	1481	4.37	1526	4.86	1542	5.34	1573	5.80	1656	6.26	1739	6.58	1791	6.77	1827	
29	3.67	1497	4.32	1543	4.80	1559	5.27	1591	5.73	1674	6.19	1758	6.50	1811	6.69	1847	
30	3.63	1513	4.27	1560	4.74	1576	5.21	1608	5.66	1693	6.11	1777	6.42	1831	6.61	1867	

Remarks:
 Q: Total Cooling Capacity (Gross) kW
 INPUT: Power Input (including the compressor, evap. fan motor & cond. W
 DB: Dry Bulb Temperature
 WB: Wet Bulb Temperature

2AMW42U4RGC - UE MULTI 2 POSTES 4,2 KW

4. CAPACITIES AND SELECTION DATA

		Cooling Operation PERFORMANCE DATA																																																				
		OUTDOOR DB (°C)																																																				
COMBINATION (%)	IDDB (°C)	IDWB (°C)	-15				-7				0				10				15				21				25				27				30				35				40				45				50			
			Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT				
80%	21	18	2.57	1.39	0.54	198	2.57	1.39	0.54	221	2.57	1.39	0.54	245	2.86	1.54	0.54	260	2.86	1.54	0.54	291	4.34	2.34	0.54	619	4.16	2.24	0.54	651	4.00	2.15	0.54	681	3.84	2.07	0.54	712	3.63	1.95	0.54	758	3.33	1.79	0.54	805	3.08	1.66	0.54	836	2.56	1.38	0.54	913

Remarks:
 Q: Total Cooling Capacity (Gross) kW
 SHC: Sensible Heat Capacity (Gross)
 SHF: Sensible Heat Factor
 IPT: Power Input(including the compressor, evap. fan motor & cond. fan motor) W
 DB: Dry Bulb Temperature
 WB: Wet Bulb Temperature

2AMW42U4RGC - UE MULTI 2 POSTES 4,2 KW

4. CAPACITIES AND SELECTION DATA

14K (Up to 2 indoor units series)

HEATING PERFORMANCE DATA

COMBINATION (%)	INDOOR DB(°C)	OUTDOOR WB(°C)															
		-15		-10		-5		0		5		10		15		20	
		Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT
130%	15	3.25	889	3.83	917	4.25	926	4.67	945	5.08	994	5.49	1044	5.76	1075	5.93	1097
	16	3.21	896	3.78	924	4.20	933	4.62	952	5.02	1002	5.42	1053	5.69	1084	5.86	1106
	17	3.18	903	3.74	931	4.15	941	4.56	960	4.96	1011	5.36	1061	5.62	1093	5.79	1115
	18	3.14	911	3.69	939	4.10	948	4.51	968	4.90	1019	5.29	1070	5.56	1102	5.72	1124
	19	3.10	918	3.65	946	4.05	956	4.45	976	4.84	1027	5.23	1078	5.49	1111	5.66	1133
	20	3.07	925	3.61	954	4.01	964	4.41	983	4.79	1035	5.18	1087	5.44	1120	5.60	1142
	21	3.03	936	3.57	965	3.97	974	4.36	994	4.74	1047	5.12	1099	5.37	1132	5.53	1154
	22	3.00	946	3.53	975	3.92	985	4.31	1005	4.68	1058	5.05	1111	5.31	1144	5.47	1167
	23	2.96	956	3.48	986	3.87	996	4.25	1016	4.62	1070	4.99	1123	5.24	1157	5.40	1180
	24	2.93	967	3.44	997	3.82	1007	4.20	1027	4.57	1081	4.93	1136	5.18	1170	5.34	1193
	25	2.89	977	3.40	1008	3.78	1018	4.15	1039	4.51	1093	4.87	1148	5.12	1182	5.27	1206
	26	2.86	988	3.36	1019	3.73	1029	4.10	1050	4.46	1105	4.82	1161	5.06	1195	5.21	1219
	27	2.82	999	3.32	1030	3.69	1040	4.05	1062	4.41	1118	4.76	1173	5.00	1209	5.15	1233
28	2.79	1010	3.28	1041	3.64	1052	4.00	1073	4.35	1130	4.70	1186	4.94	1222	5.08	1246	
29	2.75	1021	3.24	1053	3.60	1063	3.96	1085	4.30	1142	4.64	1199	4.88	1235	5.02	1260	
30	2.72	1032	3.20	1064	3.56	1075	3.91	1097	4.25	1155	4.59	1213	4.82	1249	4.96	1274	
120%	15	3.16	847	3.72	873	4.13	882	4.54	900	4.93	947	5.33	994	5.59	1024	5.76	1045
	16	3.12	854	3.67	880	4.08	889	4.48	907	4.87	955	5.26	1002	5.53	1032	5.69	1053
	17	3.08	860	3.63	887	4.03	896	4.43	914	4.81	962	5.20	1011	5.46	1041	5.62	1062
	18	3.05	867	3.58	894	3.98	903	4.38	922	4.76	970	5.14	1019	5.40	1049	5.56	1070
	19	3.01	874	3.54	901	3.94	910	4.33	929	4.70	978	5.08	1027	5.33	1058	5.49	1079
	20	2.98	881	3.51	909	3.90	918	4.28	937	4.65	986	5.03	1035	5.28	1066	5.44	1088
	21	2.95	891	3.47	919	3.85	928	4.23	947	4.60	997	4.97	1047	5.22	1078	5.37	1099
	22	2.91	901	3.42	929	3.80	938	4.18	957	4.54	1008	4.91	1058	5.15	1090	5.31	1112
	23	2.88	911	3.38	939	3.76	948	4.13	968	4.49	1019	4.85	1070	5.09	1102	5.24	1124
	24	2.84	921	3.34	949	3.71	959	4.08	978	4.44	1030	4.79	1081	5.03	1114	5.18	1136
	25	2.81	931	3.30	960	3.67	969	4.03	989	4.38	1041	4.73	1093	4.97	1126	5.12	1149
	26	2.77	941	3.26	970	3.62	980	3.98	1000	4.33	1053	4.68	1105	4.91	1139	5.06	1161
	27	2.74	952	3.22	981	3.58	991	3.94	1011	4.28	1064	4.62	1118	4.85	1151	5.00	1174
28	2.71	962	3.18	992	3.54	1002	3.89	1022	4.23	1076	4.56	1130	4.79	1164	4.94	1187	
29	2.67	973	3.15	1003	3.50	1013	3.84	1033	4.18	1088	4.51	1142	4.73	1177	4.88	1200	
30	2.64	983	3.11	1014	3.45	1024	3.80	1045	4.13	1100	4.46	1155	4.68	1189	4.82	1213	
110%	15	3.07	830	3.61	856	4.01	864	4.40	882	4.79	928	5.17	975	5.43	1004	5.59	1024
	16	3.03	837	3.56	863	3.96	871	4.35	889	4.73	936	5.11	983	5.36	1012	5.53	1032
	17	2.99	844	3.52	870	3.91	878	4.30	896	4.67	944	5.05	991	5.30	1020	5.46	1041
	18	2.96	850	3.48	877	3.87	885	4.25	904	4.62	951	4.99	999	5.24	1029	5.40	1049
	19	2.92	857	3.44	884	3.82	893	4.20	911	4.56	959	4.93	1007	5.18	1037	5.33	1058
	20	2.89	864	3.41	891	3.78	900	4.16	918	4.52	967	4.88	1015	5.12	1045	5.28	1066
	21	2.86	874	3.36	901	3.74	910	4.11	928	4.46	977	4.82	1026	5.06	1057	5.22	1078
	22	2.83	883	3.32	911	3.69	920	4.06	939	4.41	988	4.76	1037	5.00	1068	5.15	1090
	23	2.79	893	3.28	921	3.65	930	4.01	949	4.36	999	4.71	1049	4.94	1080	5.09	1102
	24	2.76	903	3.24	931	3.61	940	3.96	959	4.31	1010	4.65	1060	4.88	1092	5.03	1114
	25	2.72	913	3.21	941	3.56	950	3.91	970	4.25	1021	4.59	1072	4.82	1104	4.97	1126
	26	2.69	923	3.17	951	3.52	961	3.87	980	4.20	1032	4.54	1084	4.77	1116	4.91	1139
	27	2.66	933	3.13	962	3.48	971	3.82	991	4.15	1043	4.49	1096	4.71	1128	4.85	1151
28	2.63	943	3.09	972	3.44	982	3.77	1002	4.10	1055	4.43	1108	4.65	1141	4.79	1164	
29	2.60	954	3.05	983	3.39	993	3.73	1013	4.05	1067	4.38	1120	4.60	1153	4.73	1177	
30	2.57	964	3.02	994	3.35	1004	3.68	1024	4.01	1078	4.33	1132	4.54	1166	4.68	1189	

2AMW42U4RGC - UE MULTI 2 POSTES 4,2 KW

4. CAPACITIES AND SELECTION DATA

COMBINATION (%)	INDOOR DB(°C)	OUTDOOR WB(°C)															
		-15		-10		-5		0		5		10		15		20	
		Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT
100%	15	2.98	806	3.50	831	3.89	839	4.28	856	4.65	901	5.02	947	5.27	975	5.43	994
	16	2.94	812	3.46	838	3.85	846	4.23	863	4.59	909	4.96	954	5.21	983	5.36	1002
	17	2.91	819	3.42	844	3.80	853	4.18	870	4.54	916	4.90	962	5.15	991	5.30	1011
	18	2.87	826	3.38	851	3.75	860	4.13	877	4.48	923	4.84	970	5.09	999	5.24	1019
	19	2.84	832	3.34	858	3.71	867	4.08	884	4.43	931	4.79	977	5.03	1007	5.18	1027
	20	2.81	839	3.31	865	3.67	874	4.04	891	4.39	938	4.74	985	4.98	1015	5.12	1035
	21	2.78	848	3.27	874	3.63	883	3.99	901	4.33	949	4.68	996	4.92	1026	5.06	1047
	22	2.74	857	3.23	884	3.59	893	3.94	911	4.28	959	4.63	1007	4.86	1037	5.00	1058
	23	2.71	867	3.19	894	3.54	903	3.89	921	4.23	970	4.57	1018	4.80	1049	4.94	1070
	24	2.68	876	3.15	904	3.50	913	3.85	931	4.18	980	4.52	1029	4.74	1060	4.88	1081
	25	2.65	886	3.11	914	3.46	923	3.80	942	4.13	991	4.46	1041	4.68	1072	4.82	1093
	26	2.61	896	3.07	924	3.42	933	3.75	952	4.08	1002	4.41	1052	4.63	1084	4.77	1105
	27	2.58	906	3.04	934	3.38	943	3.71	962	4.03	1013	4.35	1064	4.57	1096	4.71	1118
	28	2.55	916	3.00	944	3.34	954	3.66	973	3.98	1024	4.30	1075	4.52	1108	4.65	1130
29	2.52	926	2.97	954	3.30	964	3.62	984	3.94	1035	4.25	1087	4.46	1120	4.60	1142	
30	2.49	936	2.93	965	3.26	975	3.58	995	3.89	1047	4.20	1099	4.41	1132	4.54	1155	
90%	15	2.87	791	3.38	816	3.76	824	4.13	841	4.49	885	4.84	929	5.09	957	5.24	976
	16	2.84	798	3.34	822	3.71	831	4.08	848	4.43	892	4.79	937	5.03	965	5.18	984
	17	2.80	804	3.30	829	3.67	837	4.03	855	4.38	900	4.73	945	4.97	973	5.12	992
	18	2.77	811	3.26	836	3.62	844	3.98	861	4.33	907	4.67	952	4.91	981	5.05	1000
	19	2.74	817	3.22	843	3.58	851	3.93	868	4.28	914	4.62	960	4.85	989	4.99	1008
	20	2.71	824	3.19	849	3.54	858	3.90	875	4.23	921	4.57	968	4.80	997	4.95	1017
	21	2.68	833	3.15	859	3.50	867	3.85	885	4.18	932	4.52	978	4.74	1008	4.89	1028
	22	2.65	842	3.11	868	3.46	877	3.80	895	4.13	942	4.46	989	4.69	1019	4.83	1039
	23	2.62	851	3.08	878	3.42	887	3.76	905	4.08	952	4.41	1000	4.63	1030	4.77	1050
	24	2.58	861	3.04	887	3.38	896	3.71	915	4.03	963	4.36	1011	4.57	1041	4.71	1062
	25	2.55	870	3.00	897	3.34	906	3.67	925	3.99	973	4.30	1022	4.52	1053	4.66	1074
	26	2.52	880	2.97	907	3.30	916	3.62	935	3.94	984	4.25	1033	4.47	1064	4.60	1085
	27	2.49	889	2.93	917	3.26	926	3.58	945	3.89	995	4.20	1045	4.41	1076	4.54	1097
	28	2.46	899	2.90	927	3.22	936	3.54	955	3.84	1006	4.15	1056	4.36	1088	4.49	1109
29	2.43	909	2.86	937	3.18	947	3.49	966	3.80	1017	4.10	1068	4.31	1100	4.44	1122	
30	2.40	919	2.83	948	3.14	957	3.45	977	3.75	1028	4.05	1079	4.26	1112	4.38	1134	
80%	15	2.79	783	3.28	808	3.64	816	4.00	833	4.35	876	4.70	920	4.93	948	5.08	967
	16	2.75	790	3.24	814	3.60	822	3.96	839	4.30	883	4.64	928	4.88	955	5.02	975
	17	2.72	796	3.20	821	3.56	829	3.91	846	4.25	891	4.59	935	4.82	963	4.96	982
	18	2.69	803	3.16	827	3.51	836	3.86	853	4.20	898	4.53	943	4.76	971	4.90	990
	19	2.66	809	3.13	834	3.47	843	3.82	860	4.15	905	4.48	950	4.70	979	4.84	998
	20	2.63	816	3.09	841	3.44	849	3.78	867	4.11	912	4.44	958	4.66	987	4.80	1006
	21	2.60	825	3.06	850	3.40	859	3.73	876	4.06	922	4.38	968	4.60	997	4.74	1017
	22	2.57	834	3.02	859	3.36	868	3.69	886	4.01	932	4.33	979	4.55	1008	4.68	1029
	23	2.54	843	2.98	869	3.32	878	3.64	896	3.96	943	4.28	990	4.49	1020	4.63	1040
	24	2.51	852	2.95	878	3.28	887	3.60	905	3.91	953	4.23	1001	4.44	1031	4.57	1051
	25	2.48	861	2.91	888	3.24	897	3.56	915	3.87	964	4.18	1012	4.38	1042	4.52	1063
	26	2.45	871	2.88	898	3.20	907	3.51	925	3.82	974	4.13	1023	4.33	1054	4.46	1075
	27	2.42	881	2.84	908	3.16	917	3.47	936	3.77	985	4.08	1034	4.28	1065	4.41	1086
	28	2.39	890	2.81	918	3.12	927	3.43	946	3.73	996	4.03	1045	4.23	1077	4.36	1098
29	2.36	900	2.78	928	3.08	937	3.39	956	3.68	1007	3.98	1057	4.18	1089	4.30	1110	
30	2.33	910	2.74	938	3.05	948	3.35	967	3.64	1018	3.93	1069	4.13	1101	4.25	1123	

Remarks:
 Q: Total Cooling Capacity (Gross) kW
 INPUT: Power Input (including the compressor, evap. fan motor & cond. W
 DB: Dry Bulb Temperature
 WB: Wet Bulb Temperature

2AMW52U4RXC - UE MULTI 2 POSTES 5,2 KW

4. CAPACITIES AND SELECTION DATA

COMBINATION (%)		Cooling Operation PERFORMANCE DATA																																																											
		OUTDOOR DB (°C)																																																											
		-15				-7				0				10				15				21				25				27				30				35				40				45				50											
IDDB (°C)	ID WB (°C)	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT
100%	21	18	3.47	2.08	0.60	344	3.47	2.08	0.60	383	3.47	2.08	0.60	422	3.86	2.32	0.60	448	3.86	2.32	0.60	500	5.87	3.52	0.60	1045	5.62	3.37	0.60	1098	5.40	3.24	0.60	1149	5.19	3.12	0.60	1202	4.90	2.94	0.60	1280	4.50	2.70	0.60	1359	4.16	2.50	0.60	1411	3.45	2.07	0.60	1465							
	21	20	3.65	1.75	0.48	384	3.65	1.75	0.48	423	3.65	1.75	0.48	462	4.06	1.95	0.48	488	4.06	1.95	0.48	540	6.17	2.96	0.48	1077	5.90	2.83	0.48	1133	5.68	2.73	0.48	1185	5.46	2.62	0.48	1239	5.15	2.47	0.48	1320	4.73	2.27	0.48	1402	4.37	2.10	0.48	1455	3.63	1.74	0.48	1510							
	22	18	3.47	2.22	0.64	344	3.47	2.22	0.64	383	3.47	2.22	0.64	422	3.86	2.47	0.64	448	3.86	2.47	0.64	500	5.87	3.76	0.64	1045	5.62	3.60	0.64	1098	5.40	3.46	0.64	1149	5.19	3.32	0.64	1202	4.90	3.14	0.64	1280	4.50	2.88	0.64	1359	4.16	2.66	0.64	1411	3.45	2.21	0.64	1465							
	22	20	3.65	1.90	0.52	384	3.65	1.90	0.52	423	3.65	1.90	0.52	462	4.06	2.11	0.52	488	4.06	2.11	0.52	540	6.17	3.21	0.52	1077	5.90	3.07	0.52	1133	5.68	2.95	0.52	1185	5.46	2.84	0.52	1239	5.15	2.68	0.52	1320	4.73	2.40	0.52	1402	4.37	2.27	0.52	1455	3.63	1.89	0.52	1510							
	22	22	3.87	1.55	0.40	423	3.87	1.55	0.40	462	3.87	1.55	0.40	501	4.30	1.72	0.40	527	4.30	1.72	0.40	579	6.54	2.62	0.40	1109	6.26	2.50	0.40	1166	6.02	2.41	0.40	1220	5.79	2.31	0.40	1276	5.46	2.18	0.40	1359	5.01	2.00	0.40	1443	4.64	1.85	0.40	1498	3.85	1.54	0.40	1555							

Remarks:
 Q: Total Cooling Capacity (Gross) kW
 SHC: Sensible Heat Capacity (Gross)
 SHF: Sensible Heat Factor
 IPT: Power Input (including the compressor, evap. fan motor & cond. fan motor) W
 DB: Dry Bulb Temperature
 WB: Wet Bulb Temperature

2AMW52U4RXC - UE MULTI 2 POSTES 5,2 KW

5. CAPACITIES AND SELECTION DATA

18K(Up to 2 indoor units series)

HEATING PERFORMANCE DATA

COMBINATION (%)	INDOOR DB(°C)	OUTDOOR WB(°C)															
		-15		-10		-5		0		5		10		15		20	
		Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT
130%	15	3.76	1240	4.42	1278	4.91	1291	5.40	1318	5.87	1387	6.34	1456	6.66	1500	6.86	1530
	16	3.71	1250	4.37	1289	4.86	1302	5.34	1328	5.80	1398	6.26	1468	6.58	1512	6.77	1542
	17	3.67	1260	4.32	1299	4.80	1312	5.27	1339	5.73	1409	6.19	1480	6.50	1524	6.69	1555
	18	3.63	1270	4.27	1309	4.74	1323	5.21	1350	5.66	1421	6.12	1492	6.42	1537	6.61	1567
	19	3.58	1280	4.22	1320	4.68	1333	5.15	1361	5.60	1432	6.04	1504	6.35	1549	6.54	1580
	20	3.55	1291	4.17	1331	4.64	1344	5.10	1372	5.54	1444	5.98	1516	6.28	1561	6.47	1593
	21	3.51	1305	4.12	1345	4.58	1359	5.04	1387	5.47	1460	5.91	1533	6.21	1579	6.39	1610
	22	3.46	1319	4.07	1360	4.53	1374	4.98	1402	5.41	1476	5.84	1549	6.13	1596	6.32	1628
	23	3.42	1334	4.03	1375	4.47	1389	4.92	1417	5.34	1492	5.77	1567	6.06	1614	6.24	1646
	24	3.38	1349	3.98	1390	4.42	1404	4.86	1433	5.28	1508	5.70	1584	5.99	1631	6.17	1664
	25	3.34	1363	3.93	1406	4.37	1420	4.80	1449	5.22	1525	5.63	1601	5.91	1649	6.09	1682
	26	3.30	1378	3.88	1421	4.31	1435	4.74	1465	5.15	1542	5.57	1619	5.84	1667	6.02	1701
	27	3.26	1394	3.84	1437	4.26	1451	4.68	1481	5.09	1559	5.50	1637	5.77	1686	5.95	1719
	28	3.22	1409	3.79	1452	4.21	1467	4.63	1497	5.03	1576	5.43	1655	5.70	1704	5.88	1738
29	3.18	1424	3.74	1468	4.16	1483	4.57	1513	4.97	1593	5.37	1673	5.64	1723	5.80	1757	
30	3.14	1440	3.70	1485	4.11	1500	4.52	1530	4.91	1611	5.30	1691	5.57	1742	5.74	1777	
120%	15	3.65	1181	4.29	1217	4.77	1230	5.24	1255	5.70	1321	6.15	1387	6.46	1429	6.66	1457
	16	3.61	1190	4.24	1227	4.71	1240	5.18	1265	5.63	1332	6.08	1398	6.38	1440	6.58	1469
	17	3.56	1200	4.19	1237	4.66	1250	5.12	1275	5.56	1342	6.01	1409	6.31	1452	6.50	1481
	18	3.52	1210	4.14	1247	4.60	1260	5.06	1285	5.50	1353	5.94	1421	6.23	1463	6.42	1493
	19	3.48	1219	4.09	1257	4.55	1270	5.00	1296	5.43	1364	5.87	1432	6.16	1475	6.35	1505
	20	3.44	1229	4.05	1267	4.50	1280	4.95	1306	5.38	1375	5.81	1444	6.10	1487	6.28	1517
	21	3.40	1243	4.00	1281	4.45	1294	4.89	1321	5.31	1390	5.74	1460	6.03	1503	6.21	1533
	22	3.36	1257	3.96	1295	4.40	1308	4.83	1335	5.25	1405	5.67	1476	5.95	1520	6.13	1550
	23	3.32	1270	3.91	1310	4.34	1323	4.77	1350	5.19	1421	5.60	1492	5.88	1537	6.06	1567
	24	3.28	1284	3.86	1324	4.29	1337	4.72	1365	5.13	1437	5.54	1508	5.81	1554	5.99	1585
	25	3.24	1298	3.82	1339	4.24	1352	4.66	1380	5.06	1452	5.47	1525	5.74	1571	5.91	1602
	26	3.20	1313	3.77	1353	4.19	1367	4.60	1395	5.00	1468	5.40	1542	5.67	1588	5.84	1620
	27	3.17	1327	3.72	1368	4.14	1382	4.55	1410	4.94	1484	5.34	1559	5.61	1605	5.77	1638
	28	3.13	1342	3.68	1383	4.09	1397	4.49	1426	4.88	1501	5.27	1576	5.54	1623	5.70	1656
29	3.09	1357	3.64	1398	4.04	1413	4.44	1441	4.82	1517	5.21	1593	5.47	1641	5.64	1674	
30	3.05	1371	3.59	1414	3.99	1428	4.39	1457	4.77	1534	5.15	1611	5.41	1659	5.57	1692	
110%	15	3.54	1158	4.17	1194	4.63	1206	5.09	1230	5.53	1295	5.97	1360	6.27	1401	6.46	1429
	16	3.50	1167	4.12	1203	4.58	1215	5.03	1240	5.47	1305	5.90	1371	6.20	1412	6.38	1440
	17	3.46	1177	4.07	1213	4.52	1225	4.97	1250	5.40	1316	5.83	1382	6.13	1423	6.31	1452
	18	3.42	1186	4.02	1223	4.47	1235	4.91	1260	5.34	1327	5.76	1393	6.05	1435	6.23	1463
	19	3.38	1196	3.97	1233	4.42	1245	4.85	1270	5.27	1337	5.70	1404	5.98	1446	6.16	1475
	20	3.34	1205	3.93	1242	4.37	1255	4.80	1281	5.22	1348	5.64	1415	5.92	1458	6.10	1487
	21	3.30	1218	3.89	1256	4.32	1269	4.75	1295	5.16	1363	5.57	1431	5.85	1474	6.03	1503
	22	3.26	1232	3.84	1270	4.27	1283	4.69	1309	5.10	1378	5.51	1447	5.78	1490	5.95	1520
	23	3.23	1245	3.79	1284	4.22	1297	4.63	1323	5.04	1393	5.44	1463	5.71	1507	5.88	1537
	24	3.19	1259	3.75	1298	4.17	1311	4.58	1338	4.98	1408	5.37	1479	5.64	1523	5.81	1554
	25	3.15	1273	3.70	1312	4.12	1326	4.52	1353	4.92	1424	5.31	1495	5.57	1540	5.74	1571
	26	3.11	1287	3.66	1327	4.07	1340	4.47	1368	4.86	1439	5.25	1511	5.51	1557	5.67	1588
	27	3.07	1301	3.62	1341	4.02	1355	4.42	1383	4.80	1455	5.18	1528	5.44	1574	5.61	1605
	28	3.04	1315	3.57	1356	3.97	1370	4.36	1398	4.74	1471	5.12	1545	5.38	1591	5.54	1623
29	3.00	1330	3.53	1371	3.92	1385	4.31	1413	4.68	1488	5.06	1562	5.31	1609	5.47	1641	
30	2.96	1345	3.49	1386	3.87	1400	4.26	1429	4.63	1504	5.00	1579	5.25	1626	5.41	1659	

2AMW52U4RXC - UE MULTI 2 POSTES 5,2 KW

4. CAPACITIES AND SELECTION DATA

COMBINATION (%)	INDOOR DB(°C)	OUTDOOR WB(°C)															
		-15		-10		-5		0		5		10		15		20	
		Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT
100%	15	3.44	1124	4.05	1159	4.50	1171	4.94	1194	5.37	1257	5.80	1320	6.09	1360	6.27	1387
	16	3.40	1133	4.00	1168	4.44	1180	4.88	1204	5.31	1267	5.73	1331	6.02	1371	6.20	1398
	17	3.36	1142	3.95	1178	4.39	1189	4.82	1214	5.24	1278	5.66	1342	5.95	1382	6.13	1409
	18	3.32	1151	3.90	1187	4.34	1199	4.77	1224	5.18	1288	5.60	1352	5.88	1393	6.05	1421
	19	3.28	1161	3.86	1197	4.29	1209	4.71	1233	5.12	1298	5.53	1363	5.81	1404	5.98	1432
	20	3.25	1170	3.82	1206	4.24	1218	4.66	1243	5.07	1309	5.48	1374	5.75	1415	5.92	1444
	21	3.21	1183	3.77	1220	4.19	1232	4.61	1257	5.01	1323	5.41	1389	5.68	1431	5.85	1460
	22	3.17	1196	3.73	1233	4.14	1245	4.55	1271	4.95	1338	5.34	1405	5.61	1447	5.78	1476
	23	3.13	1209	3.68	1247	4.09	1259	4.50	1285	4.89	1352	5.28	1420	5.54	1463	5.71	1492
	24	3.09	1222	3.64	1260	4.04	1273	4.44	1299	4.83	1367	5.22	1436	5.48	1479	5.64	1508
	25	3.06	1236	3.60	1274	4.00	1287	4.39	1313	4.77	1382	5.15	1451	5.41	1495	5.57	1525
	26	3.02	1249	3.55	1288	3.95	1301	4.34	1328	4.72	1398	5.09	1467	5.35	1511	5.51	1542
	27	2.98	1263	3.51	1302	3.90	1315	4.29	1342	4.66	1413	5.03	1484	5.28	1528	5.44	1559
	28	2.95	1277	3.47	1317	3.85	1330	4.23	1357	4.60	1428	4.97	1500	5.22	1545	5.38	1576
29	2.91	1291	3.43	1331	3.81	1345	4.18	1372	4.55	1444	4.91	1516	5.16	1562	5.31	1593	
30	2.88	1305	3.39	1346	3.76	1359	4.13	1387	4.49	1460	4.85	1533	5.10	1579	5.25	1611	
90%	15	3.32	1104	3.91	1138	4.34	1149	4.77	1173	5.18	1235	5.60	1296	5.88	1335	6.05	1362
	16	3.28	1113	3.86	1147	4.29	1159	4.71	1182	5.12	1245	5.53	1307	5.81	1346	5.98	1373
	17	3.24	1122	3.81	1156	4.24	1168	4.66	1192	5.06	1255	5.47	1317	5.74	1357	5.91	1384
	18	3.20	1131	3.77	1166	4.19	1177	4.60	1202	5.00	1265	5.40	1328	5.67	1368	5.84	1395
	19	3.16	1140	3.72	1175	4.14	1187	4.55	1211	4.94	1275	5.34	1339	5.60	1379	5.77	1406
	20	3.13	1149	3.69	1185	4.10	1197	4.50	1221	4.89	1285	5.28	1349	5.55	1390	5.71	1418
	21	3.10	1162	3.64	1198	4.05	1210	4.45	1234	4.83	1299	5.22	1364	5.48	1405	5.65	1433
	22	3.06	1174	3.60	1211	4.00	1223	4.39	1248	4.78	1314	5.16	1379	5.42	1421	5.58	1449
	23	3.02	1187	3.56	1224	3.95	1236	4.34	1262	4.72	1328	5.10	1395	5.35	1436	5.51	1465
	24	2.99	1200	3.51	1238	3.90	1250	4.29	1276	4.66	1343	5.03	1410	5.29	1452	5.45	1481
	25	2.95	1214	3.47	1251	3.86	1264	4.24	1290	4.61	1357	4.97	1425	5.22	1468	5.38	1497
	26	2.91	1227	3.43	1265	3.81	1278	4.19	1304	4.55	1372	4.91	1441	5.16	1484	5.32	1514
	27	2.88	1240	3.39	1279	3.76	1292	4.14	1318	4.50	1388	4.86	1457	5.10	1501	5.25	1531
	28	2.84	1254	3.35	1293	3.72	1306	4.09	1333	4.44	1403	4.80	1473	5.04	1517	5.19	1547
29	2.81	1268	3.31	1307	3.67	1320	4.04	1347	4.39	1418	4.74	1489	4.98	1534	5.13	1564	
30	2.78	1282	3.27	1322	3.63	1335	3.99	1362	4.34	1434	4.68	1505	4.92	1551	5.06	1582	
80%	15	3.22	1093	3.79	1127	4.21	1138	4.63	1161	5.03	1222	5.43	1283	5.70	1322	5.87	1348
	16	3.18	1102	3.74	1136	4.16	1147	4.57	1171	4.97	1232	5.37	1294	5.63	1333	5.80	1359
	17	3.14	1110	3.70	1145	4.11	1156	4.52	1180	4.91	1242	5.30	1304	5.57	1343	5.73	1370
	18	3.11	1119	3.65	1154	4.06	1166	4.46	1189	4.85	1252	5.24	1315	5.50	1354	5.67	1381
	19	3.07	1128	3.61	1163	4.01	1175	4.41	1199	4.79	1262	5.18	1325	5.44	1365	5.60	1392
	20	3.04	1138	3.58	1173	3.97	1185	4.37	1209	4.75	1272	5.13	1336	5.38	1376	5.54	1404
	21	3.00	1150	3.53	1186	3.93	1198	4.31	1222	4.69	1286	5.06	1351	5.32	1391	5.48	1419
	22	2.97	1163	3.49	1199	3.88	1211	4.26	1235	4.63	1301	5.00	1366	5.25	1407	5.41	1435
	23	2.93	1176	3.45	1212	3.83	1224	4.21	1249	4.58	1315	4.94	1381	5.19	1422	5.35	1450
	24	2.90	1188	3.41	1225	3.79	1238	4.16	1263	4.52	1329	4.88	1396	5.13	1438	5.28	1466
	25	2.86	1202	3.37	1239	3.74	1251	4.11	1277	4.47	1344	4.83	1411	5.07	1453	5.22	1483
	26	2.83	1215	3.33	1252	3.70	1265	4.06	1291	4.41	1359	4.77	1427	5.01	1469	5.16	1499
	27	2.79	1228	3.29	1266	3.65	1279	4.01	1305	4.36	1374	4.71	1442	4.95	1486	5.09	1515
	28	2.76	1242	3.25	1280	3.61	1293	3.96	1319	4.31	1389	4.65	1458	4.89	1502	5.03	1532
29	2.73	1255	3.21	1294	3.56	1307	3.92	1334	4.26	1404	4.60	1474	4.83	1518	4.97	1549	
30	2.69	1269	3.17	1308	3.52	1322	3.87	1348	4.21	1419	4.54	1490	4.77	1535	4.91	1566	

Remarks:
 Q: Total Cooling Capacity (Gross) kW
 INPUT: Power Input (including the compressor, evap. fan motor & cond. W
 DB: Dry Bulb Temperature
 WB: Wet Bulb Temperature

3AMW72U4RJC - UE MULTI 3 POSTES 7,2 KW

4. CAPACITIES AND SELECTION DATA

		Cooling Operation PERFORMANCE DATA																																																									
		OUTDOOR DB (°C)																																																									
COMBINATION (%)	IDDB (°C)	ID WB (°C)	-15				-7				0				10				15				21				25				27				30				35				40				45				50								
			Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q
100%	21	18	4.86	2.92	0.60	470	4.86	2.92	0.60	523	4.86	2.92	0.60	575	5.40	3.24	0.60	610	5.40	3.24	0.60	680	8.22	4.93	0.60	1412	7.86	4.72	0.60	1485	7.56	4.54	0.60	1553	7.27	4.36	0.60	1624	6.86	4.12	0.60	1730	6.30	3.78	0.60	1837	5.83	3.50	0.60	1907	4.83	2.90	0.60	1980					
	21	20	5.11	2.45	0.48	510	5.11	2.45	0.48	563	5.11	2.45	0.48	615	5.68	2.73	0.48	650	5.68	2.73	0.48	720	8.64	4.15	0.48	1445	8.27	3.97	0.48	1519	7.95	3.82	0.48	1589	7.64	3.67	0.48	1662	7.21	3.46	0.48	1770	6.62	3.18	0.48	1880	6.12	2.94	0.48	1951	5.08	2.44	0.48	2025					
	32	26	6.03	3.38	0.56	629	6.03	3.38	0.56	682	6.03	3.38	0.56	734	6.70	3.75	0.56	769	6.70	3.75	0.56	839	10.19	5.71	0.56	1542	9.75	5.46	0.56	1621	9.38	5.25	0.56	1696	9.02	5.05	0.56	1774	8.51	4.76	0.56	1889	7.81	4.37	0.56	2006	7.22	4.04	0.56	2082	6.00	3.36	0.56	2161					

Remarks:
 Q: Total Cooling Capacity (Gross) kW
 SHC: Sensible Heat Capacity (Gross)
 SHF: Sensible Heat Factor
 IPT: Power Input (including the compressor, evap. fan motor & cond. fan motor) W
 DB: Dry Bulb Temperature
 WB: Wet Bulb Temperature

3AMW72U4RJC - UE MULTI 3 POSTES 7,2 KW

4. CAPACITIES AND SELECTION DATA

COMBINATION (%)		Cooling Operation PERFORMANCE DATA																																																					
		OUTDOOR DB (°C)																																																					
		IDDB (°C)	ID WB (°C)	-15				-7				0				10				15				21				25				27				30				35				40				45				50			
Q	SHC			SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC	SHF	IPT	Q	SHC
90%	21	18	4.57	2.56	0.56	441	4.57	2.56	0.56	490	4.57	2.56	0.56	539	5.08	2.85	0.56	572	5.08	2.85	0.56	638	7.73	4.33	0.56	1326	7.39	4.15	0.56	1395	7.11	3.99	0.56	1459	6.84	3.83	0.56	1526	6.45	3.62	0.56	1625	5.92	3.32	0.56	1726	5.48	3.07	0.56	1791	4.54	2.55	0.56	1859	
	21	20	4.81	2.12	0.44	481	4.81	2.12	0.44	530	4.81	2.12	0.44	579	5.34	2.35	0.44	612	5.34	2.35	0.44	678	8.12	3.58	0.44	1359	7.77	3.43	0.44	1429	7.47	3.29	0.44	1495	7.18	3.17	0.44	1563	6.78	2.99	0.44	1665	6.22	2.74	0.44	1768	5.76	2.54	0.44	1835	4.78	2.11	0.44	1905	
	22	18	4.57	2.75	0.60	441	4.57	2.75	0.60	490	4.57	2.75	0.60	539	5.08	3.05	0.60	572	5.08	3.05	0.60	638	7.73	4.64	0.60	1326	7.39	4.44	0.60	1395	7.11	4.27	0.60	1459	6.84	4.11	0.60	1526	6.45	3.88	0.60	1625	5.92	3.56	0.60	1726	5.48	3.29	0.60	1791	4.54	2.73	0.60	1859	

Remarks:
 Q: Total Cooling Capacity (Gross) kW
 SHC: Sensible Heat Capacity (Gross)
 SHF: Sensible Heat Factor
 IPT: Power Input (including the compressor, evap. fan motor & cond. fan motor) W
 DB: Dry Bulb Temperature
 WB: Wet Bulb Temperature

3AMW72U4RJC - UE MULTI 3 POSTES 7,2 KW

4. CAPACITIES AND SELECTION DATA

24K (Up to 3 IDUs)

HEATING PERFORMANCE DATA

COMBINATION (%)	INDOOR DB(°C)	OUTDOOR WB(°C)															
		-15		-10		-5		0		5		10		15		20	
		Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT
130%	15	5.78	1872	6.80	1930	7.56	1949	8.31	1989	9.03	2093	9.75	2198	10.24	2264	10.55	2309
	16	5.71	1887	6.72	1945	7.47	1965	8.21	2005	8.92	2110	9.64	2216	10.12	2282	10.42	2328
	17	5.65	1902	6.64	1961	7.38	1981	8.11	2021	8.82	2127	9.52	2234	10.00	2301	10.30	2347
	18	5.58	1917	6.56	1977	7.29	1997	8.01	2037	8.71	2145	9.41	2252	9.88	2319	10.18	2366
	19	5.51	1933	6.49	1993	7.21	2013	7.92	2054	8.61	2162	9.30	2270	9.76	2338	10.05	2385
	20	5.46	1948	6.42	2009	7.14	2029	7.84	2070	8.52	2179	9.21	2288	9.67	2357	9.96	2404
	21	5.39	1970	6.35	2031	7.05	2051	7.75	2093	8.42	2203	9.09	2313	9.55	2383	9.84	2430
	22	5.33	1991	6.27	2053	6.97	2074	7.65	2116	8.32	2227	8.99	2339	9.43	2409	9.72	2457
	23	5.26	2013	6.19	2076	6.88	2097	7.56	2139	8.22	2252	8.88	2365	9.32	2435	9.60	2484
	24	5.20	2035	6.12	2098	6.80	2120	7.47	2163	8.12	2277	8.77	2391	9.21	2462	9.49	2512
	25	5.14	2058	6.05	2122	6.72	2143	7.38	2187	8.02	2302	8.67	2417	9.10	2489	9.37	2539
	26	5.08	2081	5.97	2145	6.64	2167	7.29	2211	7.93	2327	8.56	2443	8.99	2517	9.26	2567
	27	5.02	2103	5.90	2168	6.56	2190	7.21	2235	7.83	2353	8.46	2470	8.88	2544	9.15	2595
	28	4.96	2127	5.83	2192	6.48	2214	7.12	2260	7.74	2379	8.36	2498	8.78	2572	9.04	2624
29	4.90	2150	5.76	2216	6.40	2239	7.03	2285	7.65	2405	8.26	2525	8.67	2601	8.93	2653	
30	4.84	2174	5.69	2241	6.32	2263	6.95	2310	7.55	2431	8.16	2553	8.57	2629	8.82	2682	
120%	15	5.61	1783	6.61	1838	7.34	1856	8.06	1894	8.77	1994	9.47	2093	9.94	2156	10.24	2199
	16	5.55	1797	6.53	1852	7.25	1871	7.97	1909	8.66	2010	9.36	2110	9.82	2174	10.12	2217
	17	5.48	1811	6.45	1867	7.17	1886	7.87	1925	8.56	2026	9.24	2127	9.71	2191	10.00	2235
	18	5.42	1826	6.37	1882	7.08	1901	7.78	1940	8.46	2042	9.13	2145	9.59	2209	9.88	2253
	19	5.35	1841	6.30	1898	7.00	1917	7.69	1956	8.36	2059	9.03	2162	9.48	2227	9.76	2271
	20	5.30	1856	6.24	1913	6.93	1932	7.61	1972	8.28	2075	8.94	2179	9.38	2245	9.67	2290
	21	5.24	1876	6.16	1934	6.84	1954	7.52	1993	8.18	2098	8.83	2203	9.27	2269	9.55	2315
	22	5.17	1897	6.09	1955	6.76	1975	7.43	2015	8.08	2121	8.72	2227	9.16	2294	9.43	2340
	23	5.11	1917	6.01	1977	6.68	1997	7.34	2037	7.98	2145	8.62	2252	9.05	2320	9.32	2366
	24	5.05	1939	5.94	1999	6.60	2019	7.25	2060	7.88	2168	8.52	2277	8.94	2345	9.21	2392
	25	4.99	1960	5.87	2021	6.52	2041	7.17	2083	7.79	2192	8.41	2302	8.83	2371	9.10	2418
	26	4.93	1981	5.80	2043	6.44	2063	7.08	2105	7.70	2216	8.31	2327	8.73	2397	8.99	2445
	27	4.87	2003	5.73	2065	6.37	2086	7.00	2129	7.60	2241	8.21	2353	8.62	2423	8.88	2472
	28	4.81	2025	5.66	2088	6.29	2109	6.91	2152	7.51	2265	8.11	2379	8.52	2450	8.78	2499
29	4.75	2048	5.59	2111	6.21	2132	6.83	2176	7.42	2290	8.02	2405	8.42	2477	8.67	2526	
30	4.70	2070	5.53	2134	6.14	2156	6.75	2200	7.33	2315	7.92	2431	8.32	2504	8.57	2554	
110%	15	5.45	1748	6.41	1802	7.13	1820	7.83	1857	8.51	1955	9.19	2052	9.65	2114	9.94	2156
	16	5.39	1762	6.34	1816	7.04	1834	7.74	1872	8.41	1970	9.08	2069	9.54	2131	9.82	2174
	17	5.32	1776	6.26	1831	6.96	1849	7.65	1887	8.31	1986	8.98	2086	9.42	2148	9.71	2191
	18	5.26	1790	6.19	1846	6.87	1864	7.55	1902	8.21	2002	8.87	2102	9.31	2166	9.59	2209
	19	5.20	1805	6.11	1860	6.79	1879	7.47	1918	8.11	2019	8.76	2119	9.20	2183	9.48	2227
	20	5.15	1819	6.05	1875	6.73	1894	7.39	1933	8.03	2035	8.68	2137	9.11	2201	9.38	2245
	21	5.08	1839	5.98	1896	6.65	1915	7.30	1954	7.94	2057	8.57	2160	9.00	2225	9.27	2269
	22	5.02	1859	5.91	1917	6.57	1936	7.21	1976	7.84	2080	8.47	2184	8.89	2249	9.16	2294
	23	4.96	1880	5.84	1938	6.49	1958	7.13	1998	7.75	2103	8.37	2208	8.79	2274	9.05	2320
	24	4.90	1901	5.77	1959	6.41	1979	7.04	2020	7.66	2126	8.27	2232	8.68	2299	8.94	2345
	25	4.84	1921	5.70	1981	6.33	2001	6.96	2042	7.56	2149	8.17	2257	8.58	2324	8.83	2371
	26	4.79	1943	5.63	2003	6.26	2023	6.87	2064	7.47	2173	8.07	2281	8.47	2350	8.73	2397
	27	4.73	1964	5.56	2025	6.18	2045	6.79	2087	7.38	2197	7.97	2307	8.37	2376	8.62	2423
	28	4.67	1986	5.50	2047	6.11	2068	6.71	2110	7.29	2221	7.88	2332	8.27	2402	8.52	2450
29	4.62	2007	5.43	2069	6.03	2090	6.63	2133	7.21	2245	7.78	2358	8.17	2428	8.42	2477	
30	4.56	2029	5.37	2092	5.96	2113	6.55	2157	7.12	2270	7.69	2384	8.07	2455	8.32	2504	

3AMW72U4RJC - UE MULTI 3 POSTES 7,2 KW

4. CAPACITIES AND SELECTION DATA

COMBINATION (%)	INDOOR DB(°C)	OUTDOOR WB(°C)															
		-15		-10		-5		0		5		10		15		20	
		Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT
100%	15	5.29	1697	6.23	1749	6.92	1767	7.60	1803	8.26	1898	8.92	1993	9.37	2052	9.65	2093
	16	5.23	1710	6.15	1763	6.84	1781	7.51	1817	8.17	1913	8.82	2009	9.26	2069	9.54	2110
	17	5.17	1724	6.08	1777	6.75	1795	7.42	1832	8.07	1928	8.71	2025	9.15	2086	9.42	2127
	18	5.11	1738	6.01	1792	6.67	1810	7.33	1847	7.97	1944	8.61	2041	9.04	2102	9.31	2145
	19	5.05	1752	5.94	1806	6.60	1824	7.25	1862	7.88	1960	8.51	2058	8.93	2119	9.20	2162
	20	5.00	1766	5.88	1821	6.53	1839	7.18	1877	7.80	1976	8.42	2074	8.85	2137	9.11	2179
	21	4.94	1786	5.81	1841	6.45	1859	7.09	1897	7.71	1997	8.32	2097	8.74	2160	9.00	2203
	22	4.88	1805	5.74	1861	6.37	1880	7.00	1918	7.61	2019	8.22	2120	8.63	2184	8.89	2227
	23	4.82	1825	5.67	1882	6.30	1901	6.92	1939	7.52	2041	8.12	2144	8.53	2208	8.79	2252
	24	4.76	1845	5.60	1902	6.22	1921	6.84	1961	7.43	2064	8.03	2167	8.43	2232	8.68	2277
	25	4.70	1865	5.53	1923	6.15	1943	6.76	1982	7.34	2087	7.93	2191	8.33	2257	8.58	2302
	26	4.65	1886	5.47	1944	6.07	1964	6.67	2004	7.25	2110	7.84	2215	8.23	2281	8.47	2327
	27	4.59	1907	5.40	1966	6.00	1986	6.59	2026	7.17	2133	7.74	2239	8.13	2307	8.37	2353
	28	4.54	1928	5.34	1987	5.93	2007	6.52	2048	7.08	2156	7.65	2264	8.03	2332	8.27	2379
29	4.48	1949	5.27	2009	5.86	2030	6.44	2071	7.00	2180	7.56	2289	7.93	2358	8.17	2405	
30	4.43	1970	5.21	2031	5.79	2052	6.36	2094	6.91	2204	7.47	2314	7.84	2384	8.07	2431	
90%	15	5.11	1666	6.01	1718	6.68	1735	7.34	1770	7.97	1864	8.61	1957	9.04	2015	9.31	2056
	16	5.05	1680	5.94	1732	6.60	1749	7.25	1785	7.88	1879	8.51	1973	8.94	2032	9.20	2072
	17	4.99	1693	5.87	1745	6.52	1763	7.16	1799	7.79	1894	8.41	1988	8.83	2048	9.09	2089
	18	4.93	1707	5.80	1760	6.44	1777	7.08	1814	7.69	1909	8.31	2004	8.72	2065	8.99	2106
	19	4.87	1721	5.73	1774	6.36	1792	6.99	1828	7.60	1924	8.21	2021	8.62	2081	8.88	2123
	20	4.82	1734	5.67	1788	6.30	1806	6.92	1843	7.53	1940	8.13	2037	8.54	2098	8.79	2140
	21	4.76	1753	5.60	1808	6.23	1826	6.84	1863	7.44	1961	8.03	2059	8.43	2121	8.69	2164
	22	4.71	1773	5.54	1828	6.15	1846	6.76	1884	7.35	1983	7.94	2082	8.33	2144	8.58	2187
	23	4.65	1792	5.47	1848	6.08	1866	6.68	1904	7.26	2005	7.84	2105	8.23	2168	8.48	2211
	24	4.59	1812	5.40	1868	6.00	1887	6.60	1925	7.17	2027	7.75	2128	8.13	2192	8.38	2236
	25	4.54	1832	5.34	1889	5.93	1908	6.52	1947	7.09	2049	7.65	2151	8.04	2216	8.28	2260
	26	4.48	1852	5.28	1909	5.86	1929	6.44	1968	7.00	2072	7.56	2175	7.94	2240	8.18	2285
	27	4.43	1872	5.21	1930	5.79	1950	6.36	1990	6.92	2094	7.47	2199	7.84	2265	8.08	2310
	28	4.38	1893	5.15	1952	5.72	1971	6.29	2012	6.83	2117	7.38	2223	7.75	2290	7.98	2336
29	4.32	1914	5.09	1973	5.65	1993	6.21	2034	6.75	2141	7.29	2248	7.66	2315	7.89	2361	
30	4.27	1935	5.03	1995	5.58	2015	6.14	2056	6.67	2164	7.20	2272	7.56	2341	7.79	2387	
80%	15	4.95	1649	5.83	1700	6.48	1718	7.12	1753	7.73	1845	8.35	1937	8.77	1995	9.03	2035
	16	4.89	1663	5.76	1714	6.40	1732	7.03	1767	7.64	1860	8.25	1953	8.67	2011	8.93	2052
	17	4.84	1676	5.69	1728	6.32	1745	6.95	1781	7.55	1875	8.16	1969	8.56	2028	8.82	2068
	18	4.78	1690	5.62	1742	6.25	1760	6.87	1795	7.46	1890	8.06	1984	8.46	2044	8.72	2085
	19	4.72	1703	5.56	1756	6.17	1774	6.78	1810	7.37	1905	7.96	2000	8.36	2060	8.61	2102
	20	4.68	1717	5.50	1770	6.11	1788	6.72	1825	7.30	1921	7.89	2017	8.28	2077	8.53	2119
	21	4.62	1736	5.44	1790	6.04	1808	6.64	1845	7.21	1942	7.79	2039	8.18	2100	8.43	2142
	22	4.56	1755	5.37	1809	5.97	1828	6.56	1865	7.13	1963	7.70	2061	8.08	2123	8.32	2165
	23	4.51	1774	5.31	1829	5.90	1848	6.48	1885	7.04	1985	7.60	2084	7.99	2146	8.22	2189
	24	4.46	1794	5.24	1849	5.82	1868	6.40	1906	6.96	2006	7.51	2107	7.89	2170	8.13	2213
	25	4.40	1814	5.18	1870	5.75	1889	6.32	1927	6.87	2029	7.42	2130	7.79	2194	8.03	2238
	26	4.35	1834	5.12	1890	5.69	1909	6.25	1948	6.79	2051	7.33	2153	7.70	2218	7.93	2262
	27	4.30	1854	5.06	1911	5.62	1930	6.17	1970	6.71	2073	7.25	2177	7.61	2242	7.84	2287
	28	4.25	1874	4.99	1932	5.55	1952	6.10	1991	6.63	2096	7.16	2201	7.52	2267	7.74	2312
29	4.19	1895	4.93	1953	5.48	1973	6.03	2013	6.55	2119	7.07	2225	7.43	2292	7.65	2338	
30	4.14	1916	4.88	1975	5.42	1995	5.95	2035	6.47	2143	6.99	2250	7.34	2317	7.56	2364	

Remarks:
Q: Total Cooling Capacity (Gross) **kW**
INPUT: Power Input (including the compressor, evap. fan motor & cond. **W**
DB: Dry Bulb Temperature
WB: Wet Bulb Temperature

5. CAPACITIES AND SELECTION DATA

3AMW52U4RJA - UE MULTI 3 POSTES 5,2 KW

Up to 3 IDUs

AMW3-14U4RJA/AMW3-18U4RJA

COOLING CAPACITY (W)

Indoor temperature		Outdoor temperature (°C DB)						
(°C DB)	(°C WB)	15	20	25	30	35	40	45
22	16	8036	8282	8036	7954	7790	7052	6232
27	19	8610	8774	8528	8446	8200	7380	6560
30	22	8856	9020	8774	8610	8364	7544	6724

(°C DB) : Dry Bulb Temperature (°C)

(°C WB) : Wet Bulb Temperature (°C)

HEATING CAPACITY (W)

Indoor temperature	Outdoor temperature DB (°C)							
DB (°C)	-15	-10	-5	0	5	10	15	20
16	6375	7225	8075	8500	8925	9775	10200	10285
20	5950	6800	7650	8075	8500	9350	9775	9605
24	5440	6290	7140	7565	7990	8840	9265	8840

(°C DB) : Dry Bulb Temperature (°C)

(°C WB) : Wet Bulb Temperature (°C)

5. CAPACITIES AND SELECTION DATA

Up to 4 IDUs
AMW4-27U4RAA

4AMW81U4RAA - UE MULTI 4 POSTES 8,1 KW

COOLING CAPACITY (W)

Indoor temperature		Outdoor temperature (°C DB)						
(°C DB)	(°C WB)	15	20	25	30	35	40	45
22	16	6560	6800	6880	7120	7200	6400	5360
27	19	8480	8400	8320	8160	8000	7200	5840
30	22	8400	8800	8720	8800	8960	8000	6400

(°C DB) : Dry Bulb Temperature (°C)

(°C WB) : Wet Bulb Temperature (°C)

HEATING CAPACITY (W)

Indoor temperature		Outdoor temperature DB (°C)							
DB (°C)		-15	-10	-5	0	5	10	15	20
16		5670	6300	7020	7920	8010	8100	8190	8280
20		5832	6480	7290	8100	8820	9270	9900	9720
24		6075	6750	8100	9000	9900	10350	11070	8820

(°C DB) : Dry Bulb Temperature (°C)

(°C WB) : Wet Bulb Temperature (°C)

AMW4-36U4RAA

4AMW105U4RAA - UE MULTI 4 POSTES 10,5 KW

COOLING CAPACITY (kW)

Indoor temperature		Outdoor temperature (°C DB)						
(°C DB)	(°C WB)	15	20	25	30	35	40	45
22	16	8200	8500	8600	8900	9000	8000	6700
27	19	10600	10500	10400	10200	10000	9000	7300
30	22	10500	11000	10900	11000	11200	10000	8000

(°C DB) : Dry Bulb Temperature (°C)

(°C WB) : Wet Bulb Temperature (°C)

HEATING CAPACITY (W)

Indoor temperature		Outdoor temperature DB (°C)							
DB (°C)		-15	-10	-5	0	5	10	15	20
16		6930	7700	8580	9680	9790	9900	10010	10120
20		7128	7920	8910	9900	10780	11330	12100	11880
24		7425	8250	9900	11000	12100	12650	13530	10780

(°C DB) : Dry Bulb Temperature (°C)

(°C WB) : Wet Bulb Temperature (°C)

Up to 5 IDUs

5AMW125U4RTA - UE MULTI 5 POSTES 12,5 KW

AMW5-42U4RTA

COOLING CAPACITY (W)

Indoor temperature		Outdoor temperature (°C DB)						
(°C DB)	(°C WB)	15	20	25	30	35	40	45
22	16	10250	10625	10750	11125	11250	10000	8375
27	19	13250	13125	13000	12750	12500	11250	9125
30	22	13125	13750	13625	13750	14000	12500	10000

(°C DB) : Dry Bulb Temperature (°C)

(°C WB) : Wet Bulb Temperature (°C)

5. CAPACITIES AND SELECTION DATA

HEATING CAPACITY (W)

Indoor temperature DB (°C)	Outdoor temperature DB (°C)							
	-15	-10	-5	0	5	10	15	20
16	8505	9450	10530	11880	12015	12150	12285	12420
20	8748	9720	10935	12150	13230	13905	14850	14580
24	9113	10125	12150	13500	14850	15525	16605	13230

(°C DB) : Dry Bulb Temperature (°C)

(°C WB) : Wet Bulb Temperature (°C)