#### **CMEV** air handling unit

## 11061080

VEX500 is the air handling unit solution that delivers very good indoor air quality (ePM1 filter 90%) and a high level of comfort while limiting energy losses to a minimum.



#### PRODUCT BENEFITS

- air handling units producing very high efficiency (up to 95%),
  exclusive Aldes Smart Control® system,
- optimal air quality and thermal comfort

# REGULATIONS AND COMPLIANCES Eurovent Certification no.: 13.03.001

#### **Principles of operation**

VEX500 brings fresh, filtered air (up to 90% of PM1) into the building and recovers heat from exhaust air using its very high-efficiency heat exchanger. The incoming air can be heated and/or cooled using a full range of coils.

#### **Product description**

VEX400 is the ideal high-performance solution for small non-residential buildings. Thanks to its very high-performance heat exchanger, its wide range of filters and coils, building occupants enjoy very good indoor air quality (up to ePM1 90%) alongside excellent thermal and acoustic comfort. VEX400 also severely restricts energy losses to a minimum (up to 95% efficiency on Eurovent AAHE-certified heat exchanger).

#### **Fields of application**

New, Refurbishment, Non-residential buildings

#### Installation

- equipment rooms / flat roofs,
- indoors /outdoors,
- in-line duct connections,
- rectangular connectors (circular adapters available as accessories),
- choice of utility connections side left or right.

#### **Main characteristics**

- pre-wired monobloc unit featuring self-supporting construction with dual-wall panels,
- 50 mm mineral wool insulation, density 40 kg/m3,
- high-efficiency counterflow plate heat exchanger up to 95% (AAHU-certified),
- EC motor and high-performance backward curve impeller,
- 100 % and adjustable bypass control,
- G4 filters (Coarse 60%) on exhaust and F7 (ePM1 60%) on fresh air as standard,
- optional: M5 (ePM10 50%), F9 (ePM1 90%),
- wide range of coils,
- built-in switch,
- Aldes Smart Control® system:
- constant speed,
- constant airflow,
- constant pressure,
- variable airflow according to CO2/VOC sensor (0-10 V signal),
- pressure control: adapts pressure to airflow measured, for very high energy efficiency,
- built-in clock: timer control.
- configuration & monitoring via:
- remote touch-screen control,
- built-in webserver,
- BMS via ModbusRTU, Bacnet, TCP/IP.
- de-icing by electrical coil on exhaust air or by controlled bypass opening





#### **CMEV** air handling unit

## 11061080

#### **Supplementary characteristics**

- coil options:
- electrical,
- electrical post-heating,
- hot water with or without 3-way valve,
- cold water with or without 3-way valve,
- reversible (hot/cold) water with or without 3-way valve.
- aluminium or galvanised steel + paint condensate collection tray on heat exchanger,
- monobloc roof piece fitted in factory for outdoor versions,
- access to all components on the main panel via hinged, removable doors, and to control system via a specific central hatch,
- steel access doors pre-coated in dark grey (RAL 7016),
- galvanised steel or pre-coated external finish (RAL 9006) depending on the version,
- M0 interior finishes made of Z275 galvanised steel.

#### **Accessories**


Description	Variants
VEX540 rain hood	11069035
Flexible sleeve rectangular/circular D500 VEX440/540	11069051
Flexible sleeve MS Pro rectangular 610x410 mm VEX440 VEX540	11069091
Rigid adapter piece VEX540	11069043
Flat adapter piece rectangular-circular VEX440/540	11072348
Motorised shut-off damper VEX440 and VEX540	11069019

#### **Filters**

Description	Variants
FILTER KIT M5 FLAT VEX640 fresh air VEX440/VEX540	11100555
F9 flat filter kit VEX540/VEX640	11100741
ePM1 flat filter 60% (F7) VEX440/VEX640 fresh air and VEX540	11069059
G4 flat filter kit VEX640an 440/540	11069067

#### **Associated services**

Commissioning



Dimensions are given as a guide only. Make your selection in the Selector VEX software to obtain the actual characteristics of your unit.





## **CMEV** air handling unit

## 11061080

### **Principles of operation**



View of airflows in a VEX500

Eclaté VEX500

