

Heat recovery ventilation unit

11081039

The SC 370 ceiling grille offers discreet aesthetics for air extraction in ventilation or air-conditioning systems.



PRODUCT BENEFITS

- aesthetic,
- replaces a 600x600 mm suspended ceiling tile.

Principles of operation

The SC 370 suspended ceiling grille is made of slotted metal sheet with 45% of free air passage to enable air return. It is installed directly on the T-bar frames.

Product description

The SC 370 ceiling grille delivers air extraction in ventilation or air-conditioning systems. Its construction in slotted sheet metal with 45% of free air passage and its white epoxy coating enable discreet installation on walls. It is installed directly on the T-bar frames.

Fields of application

New, Refurbishment, Non-residential buildings

Installation

- installed in place of 600x600 mm suspended ceiling tile, direct attachment on T-bar frame.

Main characteristics

- slotted ceiling grille with 45% free air passage,
- steel with epoxy paint RAL 9003 white 30%,
- for 600x600 mm ceiling panel on T-bar frame,
- frameless grille.
- Range of dimensions suited to standard ceiling panels 600 x 600 mm and 1200 x 600 mm (except AU 124).
- Dimensions from 100 x 100 to 1200 x 600 mm with increments of 25 mm in length & height for the extended range.

General data

Variants	Main material
11081039	Aluminium

