

## Insulated flexible plastic duct

11091418

Aesthetic insulated rigid ducts for ventilation system in individual houses.



## PRODUCT BENEFITS

- aesthetic and high-performance ducting, ideal for unit inlets and outlets,
- efficient thermal insulation for very light weight,
- easy and quick to install with sealed connectors.

## Product description

CALOGAINE ducts offer an insulated rigid ducting solution to connect ventilation terminals to the fan unit in non-heated areas of an individual house.

## Fields of application

Multi-occupancy residential housing, Individual residential housing, New, Refurbishment

## Installation

- accessories easily slotted onto duct,
- use sealed connected available separately to ensure an airtight seal.

## Main characteristics

- Insulated rigid duct,
- dimensions:
  - internal diameter  $\varnothing = 160$  mm,
  - thickness = 16 mm,
  - duct length = 2 m.
- material: PE foam,
- temperature range =  $-40 / +105^{\circ}\text{C}$ ,
- thermal insulation equivalent to 25 mm of glass wool.

## Accessories

Variants
11091419
11091420
11091421
11091422
11091298

## General data

Variants	Maximum use temperature ( $^{\circ}\text{C}$ )	Main material	Minimum use temperature ( $^{\circ}\text{C}$ )
11091418	60	PVC	-20

## Dimensional data

Variants	H (mm)	L (mm)	$\varnothing$ (mm)	Rated $\varnothing$ duct (mm)
11091418	2000	232	232	200