

Insulated flexible plastic duct

11091515

Aesthetic insulated rigid ducts for ventilation system in individual houses.



PRODUCT BENEFITS

- aesthetic and high-performance ducting, ideal for unit inlets and outlets,
- efficient thermal insulation for very light weight,
- easy and quick to install with sealed connectors.

Product description

CALOGAINE ducts offer an insulated rigid ducting solution to connect ventilation terminals to the fan unit in non-heated areas of an individual house.

Fields of application

Multi-occupancy residential housing, Individual residential housing, New, Refurbishment

Installation

- accessories easily slotted onto duct,
- use sealed connected available separately to ensure an airtight seal.

Main characteristics

- Insulated rigid duct,
- dimensions:
 - internal diameter $\varnothing = 160$ mm,
 - thickness = 16 mm,
 - duct length = 2 m.
- material: PE foam,
- temperature range = $-40 / +105^{\circ}\text{C}$,
- thermal insulation equivalent to 25 mm of glass wool.

Accessories

Variants
11091516
11091517
11091518
11091519
11091520
11091521
11091422
11091296
11091297
11091298

General data

Variants	Maximum use temperature ($^{\circ}\text{C}$)	Main material	Minimum use temperature ($^{\circ}\text{C}$)
11091515	60	PVC	-20

Dimensional data

Variants	H (mm)	L (mm)	\varnothing (mm)	Rated \varnothing duct (mm)
11091515	2000	212	212	180

Insulated flexible plastic duct

11091515