

**Connector**

## 11094111 90° BEND GALVA - D710

The 90° bend is used to change the direction of a galvanised ducting system by a 90° angle.



**Produktbeskrivelse**

The 90° bend is used to change the direction of a galvanised ducting system by a 90° angle. Up to diameter 200 mm, bends are pressed; diameter 250 to 900 are sector bends.

**Fields of application**

Multi-occupancy residential housing, New, Refurbishment, Non-residential buildings

**Installation**

- easy assembly of interlocking accessories: ducts are female, accessories are male,
- Final seal requires sealant and/or perforated strip,
- attached to duct using self-tapping screws (4 to 6 depending on diameter).

**Reference arguments**

Application:

- Changes direction of Gas CMEV ducting by 90° in non-residential and multi-occupancy residential systems

Description:

- 90° bend aluminium diameter 710 mm

**Main characteristics**


- available in diameters from 80 to 900,
- galvanised steel as per EN 10346 ensuring uniformity of coating,
- M0 fire certification.

**General data**

Variants	Main material
11094111	Galvanised steel

**Dimensional data**

Variants	Ø (mm)	Ø A (mm)
11094111	710	710



Connector

# 11094111

90° BEND GALVA - D710

Regulatory data

Variants	Fire protection rating
11094111	M0