

Ceiling diffuser**11002766****AF 704 4-way diffuser - aluminium**

The AF 704 is a square ceiling diffuser for ceiling tiles with 4 air diffusion directions, for use in commercial buildings.



AF 704 diffuser

PRODUCT BENEFITS

- filter for extraction,
- filter accessed by simply and quickly removing the central core,
- for 600 x 600 suspended ceiling tiles.

Principles of operation

The AF 704 diffuser is installed in a ceiling in place of a standard 600 x 600 mm or 675 x 675 mm ceiling tile. This aluminium square diffuser offers 4 air diffusion directions.

Product description

The AF 704 is a steel square ceiling diffuser with 4 diffusion directions for ventilation or air-conditioning systems in commercial buildings. This diffuser is made of aluminium with epoxy coating RAL 9010 white 30% gloss. It is installed flush with the ceiling in place of a standard 600 x 600 mm or 675 x 675 mm ceiling tile. It is suitable for "T-bar" or "Fine Line" suspended ceiling frames .

Fields of application

Non-residential buildings

Installation

The AF 704 diffuser is installed in place of a standard 600 x 600 mm or 675 x 675 mm ceiling tile.

Reference arguments

- AF 704 fixed square 4-way diffuser for air supply or return,
- 472 x 472 mm,
- removable core,
- aluminium with choice of epoxy coating RAL 9003,
- 32 mm wide frame,
- concealed screw attachment to neck,
- accessories: galvanised steel plenums with side connection (RE) or top connection (RT), damper (B700) and G3 pleated filter with M1 fire rating (ISO coarse 60%).

Main characteristics

- square ceiling diffuser,
- horizontal multi-direction air supply,
- 4 diffusion directions,
- outer frame and core made of profiled aluminium,
- removable exchangeable core,
- frame width 32 mm,
- epoxy coating RAL 9010 white 30% gloss,
- installation flush on ceiling in place of a standard 600 x 600 or 675 x 675 mm ceiling tile,
- suited to suspended ceiling systems e.g. T-bar, Fine Line.

Ceiling diffuser

11002766


AF 704 4-way diffuser - aluminium

Supplementary characteristics

- accessories:
 - B 700: counter-rotary damper, adjustable from front of diffuser,
 - W4 G3 pleated filter M1 fire certification for use on extraction,
 - galvanised steel connection plenum with RT or RE branch connection.

Accessories

Désignations	References
REIF plenum (5) F0 472X472 D355	11053597
RE plenum F0 472X472 D355	11053609
Bare W4 G3 filter (replacement)	11053370
RE square plenum 472x472 D355 PC cfg	11053390
RE Plenum 472x472 D355 PC Insulated 5 sides cfg	11053406



Diffuseur AF 704 TP