

**Rigid insulated duct****11091347****ALFLEX compact gas kit Ø 125**

ALFEX Compact Gas connects a boiler and a terminal on a gas CMEV system in accordance with requirements of DTU 68.3 and DTU 24.1.

**PRODUCT BENEFITS**

- duct compacted for transport and storage,
- range compliant with gas CMEV requirements,
- M0 fire certification.

**Product description**

ALFEX Compact Gas connects a boiler and a terminal on a gas CMEV system in accordance with requirements of DTU 68.3 and DTU 24.1.

**Fields of application**

Multi-occupancy residential housing, Individual residential housing, New, Refurbishment, Non-residential buildings

**Installation**

- slot-in connection with specific reducer, without reducing nozzle diameter,
- BAZ Ø 125: slot-in connection without stretching hose on BAZ Ø 125,
- BAZ Ø 120: slot-in connection using sleeve 125/120.

**Reference arguments**

Application:

- Connection between Gas CMEV boiler to terminal compliant with DTU 683 and DTU 241 requirements
- Prohibited for condensation gas CMEV
- Maximum usage temperature: 400°C

Description:

- Aluminium sheet 15/100e mm stapled in spiral form
- Packaging: 1.5 m compacted to 30 cm
- Fitted to boiler using specific reduction, without reducing nozzle diameter
- BAZ Ø 125: Slotted directly without stretching the hose on BAZ Ø 125
- BAZ Ø 120: Slotted using sleeve 125/120
- Class A1 (M0)

**Main characteristics**

- aluminium sheet 15/100e mm with spiral stapling,
- Packaging: 1,5 m compacted into 30 cm,
- M0 fire certification (A1),
- operating temperature:
  - normal: 250 °C,
  - maximum: 400 °C.
- compliant with requirements of DTU 68.3 and DTU 24.1,
- Qualigaz certification (indelible marking),
- prohibited for use on condenser gas CMEV.

**General data**

Variants	Metal thickness (mm)	Maximum use temperature (°C)
11091347	15/100e	400

Rigid insulated duct

11091347

ALFLEX compact gas kit Ø 125

## Dimensional data

Variants	L (mm)	Ø (mm)	Weight (kg)
11091347	1500	125	0.45