

11091630

ALGAINE FV FIBRE Ø 125 mm (6 m net)

Range of reinforced flexible plastic ducts for ventilation systems in individual houses.



Standard fibre-reinforced Algaine

PRODUCT BENEFITS

- high-resistance,
- available in circular and oblong versions.

Product description

Range of reinforced flexible plastic ducts for ventilation systems in individual houses. Available in different diameters from Ø 80 mm to Ø 160 mm. Practical packaging in 6 m net.

Fields of application

Individual residential housing, New, Refurbishment

Installation

- use a packing knife to cut ALGAINE to size,
- fully extend ALGAINE and limit bend effects when installing the ducts,
- use EasyClip connectors to ensure an airtight seal on connections to fan units and ventilation terminals.

Reference arguments

Application:

- Flexible plastic ducts for exhaust and heat recovery ventilation systems in individual houses, new builds or refurbishment

Description:

- Economical
- Easy to store and transport
- Fibre-reinforced version, more resistant to work site incidents
- Craft knife required to cut
- Packaged in net

Main characteristics

- standard flexible plastic duct,
- diameters:
 - Ø 80 mm,
 - Ø 100 mm,
 - Ø 125 mm,
 - Ø 150 mm,
 - Ø 160 mm,
 - 100 x 40 mm, equivalent Ø 80 mm,
 - 135 x 65 mm, equivalent Ø 125 mm,
 - 160 x 80 mm, equivalent Ø 160 mm.
- material: PVC film + polyester fibre + steel wire,
- packaging: 6 metre net,
- temperature range: -10°C / +80°C.

General data

References	Maximum use temperature (°C)	Minimum use temperature (°C)
11091630	80	-10

11091630

ALGAIN FV FIBRE Ø 125 mm (6 m net)

Dimensional data

References	L (mm)	Ø (mm)	Weight (kg)
11091630	6000	125	1,08