

11051723 ANF75 800X400 V/POS

The ANF 75 wall-mounted backdraft damper is used to create positive pressure inside a room.

ANF75 800X400 V/SURPRESS

PRODUCT BENEFITS

- regulates pressure inside a room.

Principles of operation

The vanes of the ANF 75 wall-mounted backdraft damper open and close automatically according to the pressure, to prevent undesirable air currents (backdraft function).

Product description

The ANF 75 aluminium wall-mounted backdraft damper is used to create positive pressure inside a room. Installed on the wall.

Fields of application

New, Refurbishment, Non-residential buildings

Installation

- for installation on wall inside room,
- visible screw attachment in frame.

Reference arguments


- Extruded aluminium frame, aluminium plate vanes.
- Frame: anodised aluminium, natural satin finish.
- Vanes: rough aluminium finish.
- Visible screw attachment in frame.

Main characteristics

- extruded aluminium frame and vanes,
- finishes:
- vanes: rough aluminium,
- frame: standard anodised aluminium finish with satin aspect.

Dimensional data

References	L x H (mm)
11051723	800x400



ANF 75 overpressure damper

11051723

ANF75 800X400 V/POS

Airflow data

References	Comfort airflows for $V_k < 3$ m/s and $DP < 25$ Pa (m ³ /h)
11051723	2600