

Self-balancing individual CMEV unit

11045098

Aluminium GFA grille with choice of options



Product description

The GFA aluminium grille features a peripheral frame which fully covers the damper. The specific nature of the profiles used ensures low air pressure losses and ensures total discretion of sight. The GFA grille protects and decorates GDF guillotine dampers. It is designed to be installed with the adapter and damper protruding from the wall.

Fields of application

New, Refurbishment, Non-residential buildings

Installation

- installed with the adapter and damper protruding from the wall,
- attached using:
 - clips,
 - metric screws.
- if installed using other methods, use the adjustment elements:
 - between the retainer slide and the damper (washers 1.5 mm supplied),
 - between the stud and the damper (washers / nuts supplied).

Main characteristics

- compliance:
 - EN 1634-1: E60,
 - certified and compliant with NF-S-61937.
- fixed vane core,
- horizontal aluminium vanes (pitch 25 mm),
- airflow passage 91.3%.

Options

45010
45011
PVY
RAL1
RAL2
RAL4
45021

General data

Variants	Free air passage section (cm²)	Type of finish
11045098	560 (min) - 6300 (max)	Aluminium

Dimensional data

Variants	Lmin x Hmin (mm)	Lmax x Hmax (mm)
11045098	250 x 250	800 x 800

Self-balancing individual CMEV unit

11045098

Aluminium GFA grille with choice of options