# 11019215 BAP COLOR 45/120 m3/h - Ø 125 mm - Grey

The BAP COLOR Standard Dual-Airflow terminal is ideal for refurbishment projects - it offers two airflow settings: a base airflow whatever the conditions inside the dwelling and a boost airflow activated by pulling the cord.



BAP COLOR GREY

#### PRODUCT BENEFITS

- easy installation
- grilles in various colours.
- Low noise level

#### **Principles of operation**

In a self-balanced CMEV system, the airflow is constant whatever the ambient conditions or presence in rooms.

#### **Product description**

BAP COLOR is a self-balanced extract terminal designed for utility rooms in individual houses, multi-occupancy residential housing and the non-residential market.

#### **Fields of application**

Multi-occupancy residential housing, Individual residential housing, Refurbishment

#### Installation

- BAP COLOR must be installed in wet rooms.
- the terminal must be installed at the top of a vertical wall or on the ceiling,
- the terminal must be accessible and removable,
- versions with connection shaft: D 125 mm, 116 mm and 100 mm.
- For refurbishment, install with stapled wall plate and BAP COLOR shaftless terminal.

### **Reference arguments**

Self-balanced terminal for refurbishments

#### **Main characteristics**

- self-balanced exhaust terminal, dual airflow,
- discreet aesthetics available in several colours,
- versions and accessories to meet all installation needs,
- easy to clean: control sub-assembly quick to clip on and unclip,
- pressure range: 50 150 Pa.

#### **Supplementary characteristics**

BAP COLOR comprises:

- A white plastic body
- A control element comprising a silicone membrane and a return spring,
- A decorative grille
- A circular barrel equipped with a «Roll-In» rubber seal.

#### **General data**

References	Type of control	Colour
11019215	Pull cord	Plum







# $\begin{array}{c} 11019215 \\ \text{BAP COLOR 45/120 m3/h - \emptyset 125 mm - Grey} \end{array}$


## **Dimensional data**


References	H (mm)	L (mm)	Ø connection (mm)
11019215	150	33	125

























BAP COLOR D116





BAP COLOR DO

#### **Airflow data**

References	Basic airflow (m³/h)	Boost airflow (m³/h)	Airflow (m³/h)	Pressure range (Pa)
11019215	45	120	45/120	50-150

