11091250 BS GALVA BAR 3 m - Ø 400 mm

Circular galvanised steel ducts are ideal for all types of air distribution systems.



Galvanised steel circular ducts

Galvanised steel circular duct

PRODUCT BENEFITS

Product description

Circular galvanised steel ducts are ideal for all types of air distribution systems. They are available in lengths of 3 m or 2.47 m.

Fields of application

Multi-occupancy residential housing, New, Refurbishment, Non-residential buildings

Installation

- accessories easily slotted on: ducts are female, accessories are male,
- attached using collars or perforated strip, rails, etc. (see installation accessories pages).

Reference arguments

Application:

• Used to connect any air distribution ducting.

Description:

• Galvanised steel straight, circular duct stapled in spiral pattern, length 3 m Ø400.

Main characteristics

- standard bar length: 3 m,
- storey elements (2.47 m), designed for use as risers in multi-occupancy residential buildings, are ideal for coupling with CRE storey collectors and enable faster assembly,
- range available from diameter 80 to 900.
- ribbed tubes with smooth end pieces to ensure airtight seal on rigid connections,
- M0 fire certification,
- compliance with standards NF EN 1506 and NF EN 12237.

Accessories

Désignations	References	
INSULATED COLLAR D400	11091054	
Quick Susp. cable 2 m 0-45 kg	11091064	
Quick Susp. cable 3 m 0-45 kg	11091065	
Quick Susp. cable 5 m 0-45 kg	11091093	
Inspection hatch D400 400 x 300	11091841	

Conoral data

delicial data							
	References	Free air passage section (m²)					
	11091250	0.5					

Dimensional data

References	L (mm)	Ø (mm)	Weight (kg)	
11091250	3000	400	18,934	





