

11091257

BS GALVA BAR 3 m - Ø 560 mm

Circular galvanised steel ducts are ideal for all types of air distribution systems.



Galvanised steel circular ducts

Galvanised steel circular duct

PRODUCT BENEFITS

- core range available in stock all across France,
- Aldes is the sole French manufacturer of the whole range,
- galvanisation and thickness compliant with quality standards.

Product description

Circular galvanised steel ducts are ideal for all types of air distribution systems. They are available in lengths of 3 m or 2.47 m.

Fields of application

Multi-occupancy residential housing, New, Refurbishment, Non-residential buildings

Installation

- accessories easily slotted on: ducts are female, accessories are male,
- attached using collars or perforated strip, rails, etc. (see installation accessories pages).

Reference arguments

Application:

- Used to connect any air distribution ducting

Description:

- Galvanised steel straight, circular duct stapled in spiral pattern, length 3 m Ø560

Main characteristics

- standard bar length: 3 m,
- storey elements (2.47 m), designed for use as risers in multi-occupancy residential buildings, are ideal for coupling with CRE storey collectors and enable faster assembly,
- range available from diameter 80 to 900.
- ribbed tubes with smooth end pieces to ensure airtight seal on rigid connections,
- MO fire certification,
- compliance with standards NF EN 1506 and NF EN 12237.

Accessories

Désignations	References
INSULATED COLLAR D560	11091051
Quick Susp. cable 2 m 0-45 kg	11091064
Quick Susp. cable 3 m 0-45 kg	11091065
Quick Susp. cable 5 m 0-45 kg	11091093
Inspection hatch D560 400 x 300	11091847

General data

References	Free air passage section (m ²)
11091257	0,99

Dimensional data

References	L (mm)	Ø (mm)	Weight (kg)
11091257	3000	560	28,103

11091257
BS GALVA BAR 3 m - Ø 560 mm