

## Connector

# 11063202

## CHO 30° BEND GALVA - 350x100

The oblong horizontal 30° bend is used to change the direction of an oblong ducting system by a 30° angle in the plane of the system.



30° bend oblong horizontal

### PRODUCT BENEFITS

- small size for high airflow,
- good airtight performance and controlled pressure losses,
- easy to install and maintain (no inaccessible corners).

### Product description

The oblong horizontal 30° bend is used to change the direction of an oblong ducting system by a 30° angle in the plane of the system.

### Fields of application

Multi-occupancy residential housing, New, Refurbishment, Non-residential buildings

### Installation

- easy assembly of interlocking accessories: ducts are female, accessories are male,
- Final seal requires sealant and/or perforated strip,
- attached to duct using self-tapping screws (4 to 6 depending on diameter).

### Reference arguments

Application:

- Oblong accessories for installation of ventilation systems in confined spaces (suspended ceiling, horizontal side flues conveying high airflow, etc.)
- Connection accessory to change the direction of oblong ducting by 30° in the same plane.

Description:


- Oblong horizontal bend made of galvanised steel.
- Length 350 mm and height 100 mm.

### Main characteristics


- standard dimensions (20 oblong sections),
- galvanised steel as per EN 10346 ensuring uniformity of coating,
- MO fire certification.

### Dimensional data

References	H (mm)	L (mm)
11063202	100	350



Dimensional drawing oblong horizontal 30° bend



Dimensional drawing oblong horizontal 30° bend

### Connector

# 11063202

## CHO 30° BEND GALVA - 350x100

### Regulatory data

References	Fire protection rating
11063202	M0