

Connector

11063167

CHO 45° BEND GALVA - 700x165

The oblong horizontal 45° bend is used to change the direction of an oblong ducting system by a 45° angle in the plane of the system.



45° bend oblong horizontal

PRODUCT BENEFITS

- small size for high airflow,
- good airtight performance and controlled pressure losses,
- easy to install and maintain (no inaccessible corners).

Product description

The oblong horizontal 45° bend is used to change the direction of an oblong ducting system by a 45° angle in the plane of the system.

Fields of application

Multi-occupancy residential housing, New, Refurbishment, Non-residential buildings

Installation

- easy assembly of interlocking accessories: ducts are female, accessories are male,
- Final seal requires sealant and/or perforated strip,
- attached to duct using self-tapping screws (4 to 6 depending on diameter).

Reference arguments

Application:

- Oblong accessories for installation of ventilation systems in confined spaces (suspended ceiling, horizontal side flues conveying high airflow, etc.)
- Connection accessory to change the direction of oblong ducting by 45° in the same plane.

Description:


- Oblong horizontal bend made of galvanised steel.
- Length 700 mm and height 165 mm.

Main characteristics


- standard dimensions (20 oblong sections),
- galvanised steel as per EN 10346 ensuring uniformity of coating,
- M0 fire certification.

Dimensional data

References	H (mm)	L (mm)
11063167	165	700



Dimensional drawing oblong horizontal 45° bend



Dimensional drawing oblong horizontal 45° bend

Connector

11063167

CHO 45° BEND GALVA - 700x165

Regulatory data

References	Fire protection rating
11063167	M0