Connected object

11098142
GALVA 90° pressed bend+seal - Ø 125 mm

The sealed 90° bend is used to change the direction of a galvanised ducting system by a 90° angle while delivering class C airtight performance.

PRODUCT BENEFITS
- easy and quick to install,
- class C airtight performance,
- aesthetic ducting.

Product description
The sealed 90° bend is used to change the direction of a galvanised ducting system by a 90° angle while delivering class C airtight performance. The bends are pressed up to diameter 200, from 250 to 500 they use sectors.

Fields of application
Multi-occupancy residential housing, New, Refurbishment, Non-residential buildings

Installation
- to slot in or remove an accessory, rotate it slightly in the duct,
- as an airtight seal is automatically provided by the ALDES seal, no need to use sealant or adhesive tape,
- for vertical installations especially, the use of self-tapping screws remains recommended,
- time savings in relation to ducting with standard accessories is in the range of 20 % (at least 15 to 30 seconds saved per junction for diameters 125 to 315, or at least 30 to 60 seconds saved for each accessory in these diameters),
- ALDES sealed accessories are specially designed to ensure easy connection / disconnection. The ALDES range offers class C airtight performance and low connection torque.

Reference arguments
Application:
- Adds a sealed 90° bend to ducting in non-residential or multi-occupancy residential systems.

Description:
- 90° pressed bend galvanised steel diameter 125 mm.

Main characteristics
- available in diameters from 125 to 560,
- galvanised steel as per EN 10346 ensuring uniformity of coating,
- temperature range: - 30°C à + 100°C,
- resistant to ageing (• 30 years), UV and ozone,
- M0 fire certification,
- class C airtight performance as per standard NF EN 12237.

General data

Variants	Main material
11098142	Galvanised steel

We reserve the right to make changes without notice

Connected object

11098142
GALVA 90° pressed bend+seal - Ø 125 mm

Dimensional data

Variants	Ø (mm)	Ø A (mm)
11098142	125	125



Regulatory data

Variants	Fire protection rating
11098142	M0