


Transfer grille**11045598****GGH grille bottom opening VB**

The concealed frame of the GGH grille offers elegant and discreet aesthetics, while covering the smoke control damper from the floor to the ceiling.



GGH grille bottom opening

PRODUCT BENEFITS

- offers a corridor superb aesthetic finish with alternating grilles from the floor to the ceiling,
- identical aesthetic finish for VB and VH,
- easy to maintain thanks to removable 1-metre core.

Principles of operation

The GGH grille protects and decorates the smoke control damper, from the floor to the ceiling. The lower part of its fin core can be removed for a VB damper and the upper part can be removed for a VH damper.

Product description

The GGH grille is installed in front of a VB air intake damper or a VH smoke exhaust damper. It covers a damper from the floor to the ceiling. The lower part of its 1 m core can be removed for a VB damper and the upper part can be removed for a VH damper. The frame is an edged, concealed frame to offer the corridor an exceptional visual continuity. Simply install the GGH grille directly in the wall.

Fields of application

New, Refurbishment, Non-residential buildings

Installation

- grille flush-mounted in wall,
- attachment in wall using screws (not supplied),
- do not hide the grille when installing.

Main characteristics

- compliant with fire resistance test report for OPTONE dampers:
 - fully covers the damper,
- fin core identical to that of a GFE grille,
- concealed frame: only a slim edge is visible on the front,
- flush-mounted grille,
- removable 1-metre fin core (Omega concealed clips):
 - in lower part to access VB fresh air inlet damper,
 - in upper part to access VH smoke exhaust damper,
- air passage $\geq 91.3\%$,
- available in a wide dimensional range L x H from:
 - $250 \leq L \leq 1,200$ mm,
 - $1000 \leq H \leq 2,600$ mm,
- choice of L and H dimensions according to rule:
 - L (grille) = overall width of damper + 70 mm,
 - round L up to the nearest 25 mm increment,
- finishes:
 - anodised aluminium finish as standard,
 - high-resistance epoxy paint possible depending on RAL colour desired,
- Consult us on the possibility of increasing the height of the removable core for smoke control dampers with an overall height in excess of 0.95 m.

General data

References	Type of finish
11045598	Elegance

Transfer grille

11045598

GGH grille bottom opening VB


Dimensional data

References	Lmin x Hmin (mm)	Lmax x Hmax (mm)
11045598	250 x 1000	1200 x 2600



Grille GGH esthétique installée dans un couloir

Installation visual 1



Mise en oeuvre grille GGH