

# 11091337

## LG 3M ALFLEX GAS D150

ALFLEX special Gas 0.30 connects a boiler to a terminal and/or a terminal to a riser in a gas CMEV system.



Alflex special gas 0,30

### PRODUCT BENEFITS

- range compliant with gas CMEV requirements,
- M0 fire certification.

### Product description

ALFLEX special Gas 0.30 connects a boiler to a terminal and/or a terminal to a riser in a gas CMEV system.

### Fields of application

Multi-occupancy residential housing, Individual residential housing, New, Refurbishment, Non-residential buildings

### Installation

- fit female duct to male accessory,
- use sealant or RAF vulcanisable tape to ensure an airtight seal.

### Reference arguments

Application:

- Connection between boiler and terminal, between terminal and riser in Gas CMEV systems
- Ensures good mechanical resistance between the rigid ducting and the terminal

Description:

- Aluminium plate stapled in spiral pattern, diameter 150 mm
- Thickness 30/100e mm
- Supplied in 3 m straight lengths
- Class A1 fire rating

### Main characteristics

- Aluminium sheet 30/100 mm with spiral stapling,
- packaging: 3 m straight length,
- maximum operating temperature:
  - continuous: 250 °C,
  - peak: 350 °C.
- M0 fire certification (A1).

### General data

References	Metal thickness (mm)	Free air passage section (m <sup>2</sup> )	Maximum use temperature (°C)
11091337	30/100e	0.07	350

### Dimensional data

References	L (mm)	Ø (mm)	Weight (kg)
11091337	3000	150	2.04