

Standard flexible plastic duct

11023087 MINIGAINE circular bar 3 m Ø 125 mm white

MINIGAINE ultra-flat rigid plastic ducts for ventilation system in individual houses.



PRODUCT BENEFITS

easy to install in suspended ceiling: small dimensions,
high-quality product: resists crushing and tearing, controlled pressures losses.

Product description

MINIGAINE ducts offer an oblong rigid plastic ducting solution to connect ventilation terminals to the fan unit in low-height, heated areas of an individual house.

Fields of application

Multi-occupancy residential housing, Individual residential housing, New, Refurbishment

Installation

- accessories easily slotted into ducts: fit female connectors onto male duct bars,
- use Aldes RAA or RAV adhesive tape sold separately to ensure an airtight seal,
- attached using collars or perforated strip, rails, etc. (see ingredients),
- in all cases, to prevent pressure losses and sound propagations, limit the use of bends to a minimum.

Reference arguments

Application

• Minigaine rigid plastic duct range for exhaust and heat recovery ventilation systems in individual houses, new builds or refurbishment

Description

- Ø 125 mm
- Circular
- Connection: Male duct, Female accessories
- Materials: Duct: PVC, Accessories: Shock-proof PS, white colour

Standard flexible plastic duct

11023087 MINIGAINE circular bar 3 m Ø 125 mm white

Main characteristics

- rigid plastic duct,
- diameter:
- equivalent Ø 80 mm (bar 40x100 mm),
- equivalent Ø 125 mm (bar 60x200 mm).
- materials: PVC,
- connection:
- male duct,
- female accessories.
- temperature range: $0^{\circ}C / + 60^{\circ}C$.

Accessories

3
1
)
2
1
5
9
)
1
5
1
3
9
3
6
3
3

General data

Variants	Maximum use temperature (°C)	Minimum use temperature (°C)						
11023087	60	0						
Dimensional data								

	Variants	L (mm)	Ø (mm)	Ø equivalent (mm)	Rated Ø duct (mm)	Weight (kg)	
	11023087	3000	60x200	125	200x60	2,16	