

11023971

Minigaine 3 m bar equivalent Ø 125 mm (60x200) White

MINIGAINÉ ultra-flat rigid plastic ducts for ventilation system in individual houses.



Minigaine 3m bar

PRODUCT BENEFITS

- easy to install in suspended ceiling: small dimensions,
- high-quality product: resists crushing and tearing,
- controlled pressures losses.

Product description

MINIGAINÉ ducts offer an oblong rigid plastic ducting solution to connect ventilation terminals to the fan unit in low-height, heated areas of an individual house.

Fields of application

Multi-occupancy residential housing, Individual residential housing, New, Refurbishment

Installation

- accessories easily slotted into ducts: fit female connectors onto male duct bars,
- use Aldes RAA or RAV adhesive tape sold separately to ensure an airtight seal,
- attached using collars or perforated strip, rails, etc. (see ingredients),
- in all cases, to prevent pressure losses and sound propagations, limit the use of bends to a minimum.

Reference arguments

Application:

- Minigaine rigid plastic duct range for exhaust and heat recovery ventilation systems in individual houses, new builds or refurbishment.

Description:

- Minigaine bar, 3 m white equivalent D125 (60x200),
- Connection:
 - Male duct,
 - Female accessories.
- Material:
 - Duct: PVC,
- Accessories: Shock-proof PS, white colour

11023971

Minigaine 3 m bar equivalent Ø 125 mm (60x200) White

Main characteristics

- rigid plastic duct,
- diameter:
 - equivalent Ø 80 mm (bar 40x100 mm),
 - equivalent Ø 125 mm (bar 60x200 mm).
- materials: PVC,
- connection:
 - male duct,
 - female accessories.
- temperature range: 0°C / + 60°C.

Accessories

Désignations	References
Male connector (between 2 accessories)	11023083
Plug	11023084
Female connector (between 2 bars)	11023970
Reducer	11023972
Horizontal 90° bend	11023973
Vertical 90° bend	11023974
Vertical 90° bend for terminal Ø 125 mm	11023975
Vertical mixed T-piece for terminal Ø 125 mm	11023979
Horizontal 90° T-piece	11023980
Horizontal 90° bend for duct Ø 125 mm	11023994
Duct connector Ø 125 mm	11023995
Attachment flange	11028081
2 m net Minigaine flexible connector eq. 80 mm	11023008
2 m net Minigaine flexible connector eq. 125 mm	11023009
Minigaine extension equivalent D80 length 150 white	11023046
Minigaine female connector for duct equivalent D125 white	11023086
Minigaine 0.25m extension D125 white	11023088

General data

References	Maximum use temperature (°C)	Minimum use temperature (°C)
11023971	60	0

Dimensional data

References	L (mm)	Ø (mm)	Ø equivalent (mm)	Weight (kg)
11023971	3000	60x200	125	3,6