

11091855

OPTIFLEX® circular antistatic duct black Ø 90-50 m

The first ventilation ducting for easy and reliable installation and which meets indoor air quality requirements.



Antistatic duct black

PRODUCT BENEFITS

- leaktight ducting,
- quick to install,
- strong (slab or screed).

Product description

OPTIFLEX circular ducts offer a semi-rigid plastic ducting solution to connect ventilation terminals to the fan unit in non-heated areas of an individual house. They ensure the hygiene and quality of indoor air.

Fields of application

Multi-occupancy residential housing, Individual residential housing, New, Refurbishment

Installation

- accessories easily slotted into ducts using OPTIFLEX seals sold separately,
- use OPTIFLEX seals sold separately to ensure an airtight seal,
- lyre collars or perforated strips to attach ducts available as accessories,
- in all cases, to prevent pressure losses and sound propagations, limit the use of bends to a minimum.

Main characteristics

- semi-rigid plastic ducts,
- internal/external diameter:
 - Ø 78/90 mm,
 - Ø 63/75 mm.
- material:
 - blue duct: Food-grade HDPE with anti-static treatment,
 - grey duct: Pure HDPE with anti-static and anti-bacterial (silver ion) treatments.
- Supplied in: 30 m or 50 m reel,
- Operating temperature range: -5 to +60°C.