Connector

11096521 PEC ALU - D315/355

The PEC aluminium circular 90° branch connector makes a right-angle branch on an aluminium circular duct.



Piquage Equerre Circulaire en aluminium

PRODUCT BENEFITS

Product description

The PEC aluminium circular 90° branch connector makes a right-angle branch on an aluminium circular duct.

Fields of application

Multi-occupancy residential housing, New, Refurbishment, Non-residential buildings

Installation

- when installing, pay special attention to pressures losses, noise and leaks that may be generated,
- easy assembly of interlocking accessories: ducts are female, accessories are male,
- final seal requires sealant and/or perforated strip,
- attached to duct using self-tapping screws (4 to 6 depending on diameter).

Reference arguments

Application:

• Serves to add a 90° bend diameter 355 mm to circular ducting diameter 315 mm in a gas CMEV system

Description:

Aluminium connector diameter 315/355 mm

Main characteristics

- available in diameters from 125 to 500,
- aluminium 1050A-H18 (formerly A5) compliant with DTU 68.3 for gas CMEV,
- M0 fire certification.

Dimensional data

D. Communication		GD (·····)
References	Ø A (mm)	Ø B (mm)
11096521	355	315
	V V	Ø B

Dimensional drawing Circular 90° branch connector, aluminium





CIRCULAR ALUMINIUM DUCTWORK

Connector

11096521 PEC ALU - D315/355

Regulatory data

References	Fire protection rating
11096521	M0



