# **1** GALVA RANGE

#### Connector



The PEC circular branch connector makes a 45° angle branch on a galvanised circular duct.



Piquage Oblique Circulaire 45°

### **Product description**

The PEC circular branch connector makes a 45° angle branch on a galvanised circular duct. **Fields of application** 

## Multi-occupancy residential housing, New, Refurbishment, Non-residential buildings

Installation

- when installing, pay special attention to pressures losses, noise and leaks that may be generated,
- easy assembly of interlocking accessories: ducts are female, accessories are male,
- final seal requires sealant and/or perforated strip,
- attached to duct using self-tapping screws (4 to 6 depending on diameter).

### Reference arguments

Application:

• Serves to add a 45° bend diameter 800 mm to circular ducting diameter 355 mm.

#### Description:

• Angled connector galvanised steel diameter 355/800 mm

#### Main characteristics

- available in diameters from 80 to 900,
- galvanised steel as per EN 10346 ensuring uniformity of coating,

### • M0 fire certification.

#### Dimensional data

References	Ø A (mm)	Ø B (mm)
11097284	800	355

Dimensional drawing Circular 45° angled branch connector



### Connector 11097284 POC ANGLE GALVA - D355/800

Regulatory data

References 11097284

Fire protection rating M0