#### Connector

## 11097341 POC ANGLE GALVA - D800/900

The PEC circular branch connector makes a 45° angle branch on a galvanised circular duct.



Piquage Oblique Circulaire 45°

#### **Product description**

The PEC circular branch connector makes a 45° angle branch on a galvanised circular duct.

#### **Fields of application**

Multi-occupancy residential housing, New, Refurbishment, Non-residential buildings

#### Installation

- when installing, pay special attention to pressures losses, noise and leaks that may be generated,
- easy assembly of interlocking accessories: ducts are female, accessories are male,
- final seal requires sealant and/or perforated strip,
- attached to duct using self-tapping screws (4 to 6 depending on diameter).

#### **Reference arguments**

#### Application:

• Serves to add a 45° bend diameter 900 mm to circular ducting diameter 800 mm.

#### Description:

• Angled connector galvanised steel diameter 800/900 mm

#### **Main characteristics**

- available in diameters from 80 to 900,
- galvanised steel as per EN 10346 ensuring uniformity of coating,
- M0 fire certification.

#### Dimensional data

Difficiational data		
References	Ø A (mm)	Ø B (mm)
11097341	900	800
	V <sub>Ø</sub>	

Dimensional drawing Circular 45° angled branch connector





**Connector** 

# 11097341 POC ANGLE GALVA - D800/900

### **Regulatory data**

References	Fire protection rating	
11097341	MO	



