#### Connector

# 11097364 POP GALVA FLAT CONNECTR - D250

The POP angled branch connector makes a 45° angle branch on a galvanised oblong or rectangular duct.



Piquage Oblique sur Plat 45°

# **Product description**

The POP angled branch connector makes a 45° angle branch on a galvanised oblong or rectangular duct.

## **Fields of application**

Multi-occupancy residential housing, New, Refurbishment, Non-residential buildings

#### Installation

- when installing, pay special attention to pressures losses, noise and leaks that may be generated,
- easy to assemble using interlocking parts: ducts are female in design, accessories are male,
- airtight seal formed using sealant and/or adhesive tape,
- attached to duct using self-tapping screws (4 to 6 depending on diameter).

## **Reference arguments**

#### Application:

• Serves to add a 45° bend diameter 250 mm to oblong or rectangular flat ducting.

# Description:

• Angled flat connector galvanised steel diameter 250 mm

## **Main characteristics**

- available in diameters from 80 to 900,
- galvanised steel as per EN 10346 ensuring uniformity of coating,
- M0 fire certification.

## **Dimensional data**




Schéma d'encombrement Piquage Oblique sur Plat 45°





**Connector** 

# 11097364 POP GALVA FLAT CONNECTR - D250

# **Regulatory data**

References	Fire protection rating
11097364	M0



