


## Special diffuser

11002199

Plenum LINED Combined TP



## Product description

This double plenum delivers combined air supply or extract via the LINED® Combined TP slot diffuser.

## Fields of application

New, Refurbishment, Non-residential buildings

## Installation

- concealed attachment of diffuser to plenum using screws, accessible on the sides of the diffuser,
- assembly attached to concrete slab using tabs on plenum.

## Reference arguments

• Plenum for Lined Combined TP slot diffuser. • Double compartment for very low leakage rate (<5%) on air supply/return to minimise energy losses. • Options: soundproofing or thermal and acoustic insulation (M1 fire rating), G3 filter with M1 fire rating (ISO Coarse 60%), damper, plenum length shorter than diffuser, blanking caps for blocked vision function, connection diameters, oblong connection, supplementary connection, height.

## Main characteristics

- galvanised steel,
- options:
  - number and size of connections,
  - damper,
  - thermal+acoustic insulation or soundproofing,
  - plenum supplied fitted to diffuser,
  - plenum shorter than diffuser,
  - blanking caps,
  - filter.

## Accessories

| Description         | Variants |
|---------------------|----------|
| Bag of 100 F3 clips | 21080260 |

## Options

| Options    |
|------------|
| ACOU       |
| ACOU2      |
| FILTRA     |
| MONT       |
| OBTU       |
| PIQAN3     |
| PIQPLUS3_2 |
| REGIS4     |
| THER       |
| THER2      |

Special diffuser

11002199

Plenum LINED Combined TP

Dimensional data

| Variants | H (mm) | L (mm)   |
|----------|--------|----------|
| 11002199 | 65-380 | 600-1600 |