Connector

11063967 ROCTP GALVA - 450x100 - D160

The ROCTP oblong cylindrical tangent reducer is used to connect an oblong duct with a circular duct while maintaining a linear and flat ducting without losing space underneath.



Oblong Tangent Cylindrical Reducer on flat section:

PRODUCT BENEFITS

Product description

The ROCTP oblong cylindrical tangent reducer is used to connect an oblong duct with a circular duct while maintaining a linear and flat ducting without losing space underneath.

Fields of application

Multi-occupancy residential housing, New, Refurbishment, Non-residential buildings

Installation

- easy assembly of interlocking accessories: ducts are female, accessories are male,
- Final seal requires sealant and/or perforated strip,
- attached to duct using self-tapping screws (4 to 6 depending on diameter).

Reference arguments

Application:


- Oblong accessories for installation of ventilation systems in confined spaces (suspended ceiling, horizontal side flues conveying high airflow, etc.)
- Cylindrical tangential oblong reducer used to connect oblong ducting to circular ducting while retaining a linear, flat system without losing space underneath

- ROCTP cylindrical tangential oblong reducer on flat section, galvanised steel
- Length 450 mm and height 100 mm Diameter 160 mm

Main characteristics

- standard dimensions (20 oblong sections),
- galvanised steel as per EN 10346 ensuring uniformity of coating,
- M0 fire certification.

Dimensional data









OBLONG GALVANISED DUCTWORK

Connector

11063967 ROCTP GALVA - 450x100 - D160

Regulatory data

References	Fire protection rating
11063967	MO



