1 CEILING DIFFUSERS

Collective static heat exchanger



The SC 832 TP is a steel concentric horizontal fixed air diffuser, designed to replace a standard ceiling tile.



PRODUCT BENEFITS

intended for 600x600 mm suspended ceiling tiles,
easy to install.

Principles of operation

The SC 832 diffuser is installed in the place of a standard 600x600 mm suspended ceiling tile. It delivers a horizontal fixed airflow.

Product description

The SC 832 is a fixed concentric steel diffuser for air distribution in ventilation or air conditioning systems in commercial buildings. It is designed to be installed in place of a standard 600 x 600 mm ceiling tile. The diffuser is made of steel with an epoxy paint finish, RAL 9003 white 30% gloss.

Fields of application

New, Refurbishment, Non-residential buildings

Installation

The SC 832 TP diffuser is installed in the place of a standard 600x600 mm suspended ceiling tile.

Reference arguments

- Pressed steel circular cones, fixed position.
- Steel compensation plate replacing a ceiling panel.
- Concealed screw attachment to concrete slab in diffuser neck. Note: the weight of the diffuser must not be borne by the suspended ceiling framework. Use the suspension cables on page xxx.
- Direct connection to circular ducts or LRE plenum.
- Steel finish, epoxy paint RAL 9010 white.

Main characteristics

- SC 832 fixed concentric steel diffuser,
- steel ceiling compensation plate.
- steel with epoxy paint:
- standard: white RAL 9003 30% gloss,
- option: other RAL.
- attachment:
- installed in place of a 600 x 600 mm ceiling tile.
- circular duct connection directly on neck
- connection:
- overall dimensions suited to T-bar ceiling 600 x 600 mm
- using a plenum.

Collective static heat exchanger

11051017 SC 832 TP F0 D250 (AxB=600x600)


Supplementary characteristics

- accessories:
- BR butterfly type damper with 2 V-shape vanes,
- LRE galvanised steel connection plenum.

Accessories

Description	Variants
PLENUM LRE842/883 F0 D250/250	11053313
BR CIRCULAR DAMPER D250	11053222
LRE Plenum diff circular F0 D250 PC cfg	11053348
Distribution box LRE with side connection	11053368

Dimensional data



Variants Comfort airflow < 35 dB(A) (m³/h)</th> 11051017 600