


Wall grille

11050016

SC125 F3 500X300

The SC 125 slotted grille offers discreet aesthetics for air extraction in ventilation or air-conditioning systems.



Grille SC 125

PRODUCT BENEFITS

- aesthetic,
- easy to install / remove.

Principles of operation

The SC 125 wall grille is made of slotted metal sheet with 45% of free air passage, to enable air extraction. It uses F3 clips for easy installation/removal in ME/MT plenums and has an F4 mounting frame.

Product description

The SC 125 wall grille delivers air extraction in ventilation or air-conditioning systems. Its construction in slotted sheet metal with 45% of free air passage and its white epoxy coating enable discreet installation on walls. Furthermore, its F3 clips as standard make it easy to install and remove in plenums or mounting frames.

Fields of application

New, Refurbishment, Non-residential buildings

Installation

- for installation on wall,
- grille supplied with F3 clips for easy installation / removal in ME/MT plenums or in the F4 mounting frame.

Main characteristics

- slotted wall-mounted grille with 45% free air passage,
- steel with epoxy paint finish, RAL 9003 white 30%,
- concealed F3 attachment using friction clips.
- dimensions from 75 x 75 to 1,200 x 600 mm with increments of 25 mm in length.

Accessories

Désignations	References
Adapter F4 500X300	11053789
MTF3 500X300/D315 PLENUM PA	11053658
MTF3 PLENUM PA	11053703
RECT DAMPER SGS 500X300	11053269
MT Plenum F3 500X300/D315 PA cfg	11053529

General data


References	Type of finish	Colour
11050016	Epoxy paint	Lagoon blue

Wall grille


11050016
SC125 F3 500X300

Dimensional data

References	H (mm)	L (mm)	Ø plenum (mm)
11050016	300	500	315



Grille SC 125 seule



Grille SC 125 avec registre AGB ou SGS monté

Airflow data

References	Comfort airflow for $L_w < NR 25$ (m^3/h)
11050016	1100