

Ceiling diffuser

11051172

SC319R F16 D250 500x500

The SC 319 R is a slotted plate square diffuser for extraction.



SC319R F16 D250 500x500

PRODUCT BENEFITS

- circular connection for faster installation,
- filtration for extraction.

Principles of operation

The SC 319 R diffuser is installed on a plaster or BA13 ceiling. It opens to enable easy access for installation of the filter and maintenance.

Product description

The SC 319 R is a square slotted opening air return diffuser. For installation in plaster and plasterboard (BA13) ceilings. Diffuses air in HVAC systems. This diffuser is made of steel with epoxy coating RAL 9010 white 30% gloss. It features concealed attachments and is connected directly to circular ducting.

Fields of application

Non-residential buildings

Installation

The SC 319 R diffuser is installed flush with the ceiling. Direct attachment to ducting.

Reference arguments

- Removable slotted plate.
- Steel finish, epoxy paint RAL 9010 white.
- Concealed attachment to concrete slab using F16 brackets fitted to diffuser.
- Direct connection to circular duct.

Main characteristics

- extraction diffuser,
- removable slotted plate,
- epoxy coating RAL 9010 white,
- concealed attachment to concrete slab using tabs fitted to diffuser (F16 attachment method),
- direct attachment to circular ducting.

Supplementary characteristics

- accessories:
 - G3 flat filter with M1 fire certification,
 - galvanised steel plenum with side branch connection (NE).

Accessories

Désignations	References
BR CIRCULAR DAMPER D250	11053222

Consumables

Désignations	References
G3 flat filter M1 for SC 319 and SC 369 D250	11053520


Ceiling diffuser

11051172

SC319R F16 D250 500x500

Dimensional data

References	C (mm)	F (mm)	H3 (mm)	L x H (mm)	W (mm)	Ø D (mm)
11051172	122	60	380	500x500	480	250



Diffuseur SC 319 R

Airflow data

References	Comfort airflow for Lw 40 dB(A) (extract with filter) (m³/h)	Comfort airflow for Lw 40 dB(A) (air supply) (m³/h)
11051172	650	600