

Collective static heat exchanger

11051555

SF704 F0 472X472

The SF 704 is a steel square ceiling diffuser with 4 air diffusion directions, for use in commercial buildings.



PRODUCT BENEFITS

- filter for return (optional),
- filter accessed by simply and quickly removing the central core,
- for 600 x 600 suspended ceiling tiles.

Principles of operation

The SF 704 diffuser is installed on the ceiling using visible or concealed attachments. The steel square diffuser offers 4 air diffusion directions.

Product description

The SF 704 is a steel square ceiling diffuser with 4 diffusion directions for ventilation or air-conditioning systems in commercial buildings. This diffuser is made of steel with epoxy coating RAL 9010 white 30% gloss. It is installed flush with the ceiling. Available in dimensions from 150x150 mm to 600x600 mm.

Fields of application

Non-residential buildings

Installation

The SF 704 diffuser is installed flush with the ceiling using visible or concealed attachments in the frame. A concealed screw and suspension bridge attachment system is also available and preferred for installation on fixed ceilings.

Reference arguments

- External frame and core made of assembled extruded aluminium profiles or formed steel plate.
- Spring system enabling removable core for access to interior.
- AF 704: anodised aluminium with natural satin finish or RAL 9010 white epoxy paint.
- SF 704: steel with epoxy paint finish RAL 9010 white.
- Concealed attachment to plenum using side screws in the neck.
- The plenum is fitted with brackets for attachment to a concrete slab.

Main characteristics

- square ceiling diffuser,
- multi-direction horizontal air diffusion,
- 4 diffusion directions,
- profiled steel plate outer frame and core,
- removable, exchangeable core,
- frame width 32 mm,
- epoxy coating RAL 9010 white 30% gloss,
- installed flush with ceiling,
- available in dimensions from 150x150 mm to 600x600 mm.

Collective static heat exchanger

11051555
SF704 F0 472X472

Supplementary characteristics

- accessories:
- B 700: counter-rotary damper, adjustable from front of diffuser,
- W4 G3 pleated filter M1 fire certification for use on extraction,
- galvanised steel connection plenum with RT or RE branch connection.

Accessories


Description	Variants
DAMPER B700 472X472	11051328
Bare W4 G3 filter (replacement)	11053370

Filters

Description	Variants
Filter cartridge (G3 filter included) CW4 for plenum RT and RE 472x472 mm	11053435

Dimensional data

Variants	A (mm)	B (mm)	L x H (mm)	N (mm)	P (mm)	P1 (mm)	Ø D (mm)
11051555	536	596	472X472	470	465	215	355



Airflow data

Variants	Comfort airflow for Lw 40 dB(A) (extract with filter) (m³/h)	Comfort airflow for Lw 40 dB(A) (air supply) (m³/h)
11051555	670	950