

# 11091348

## Sleeve alu D125/120 for BAZ D120

ALFEX Compact Gas connects a boiler and a terminal on a gas CMEV system in accordance with requirements of DTU 68.3 and DTU 24.1.



Alflex compact gaz 125/132

### PRODUCT BENEFITS

- duct compacted for transport and storage,
- range compliant with gas CMEV requirements,
- M0 fire certification.

### Product description

ALFEX Compact Gas connects a boiler and a terminal on a gas CMEV system in accordance with requirements of DTU 68.3 and DTU 24.1.

### Fields of application

Multi-occupancy residential housing, Individual residential housing, New, Refurbishment, Non-residential buildings

### Installation

- slot-in connection with specific reducer, without reducing nozzle diameter,
- BAZ Ø 125: slot-in connection without stretching hose on BAZ Ø 125,
- BAZ Ø 120: slot-in connection using sleeve 125/120.

### Reference arguments

Application:

- Aluminium sleeve to connect a gas boiler to a BAZ terminal in a gas CMEV system in compliance with DTU requirements

Description:

- Aluminium sleeve thickness 15/100e mm stapled in spiral form diameter 125/120 mm
- Fitted to boiler using specific reduction, without reducing nozzle diameter
- A1 fire protection rating

### Main characteristics

- aluminium sheet 15/100e mm with spiral stapling,
- Packaging: 1,5 m compacted into 30 cm,
- M0 fire certification (A1),
- operating temperature:
  - normal: 250 °C,
  - maximum: 400 °C.
- compliant with requirements of DTU 68.3 and DTU 24.1,
- Qualigaz certification (indelible marking),
- prohibited for use on condenser gas CMEV.

### General data

References	Metal thickness (mm)	Maximum use temperature (°C)
11091348	15/100e	400

### Dimensional data

References	L (mm)	Weight (kg)
11091348	90	0.055