

11091603

Standard ALGAINE Ø 125 mm (10 m net)

Range of standard flexible plastic duct for ventilation systems in individual houses.



Standard Algaine

PRODUCT BENEFITS

- economic,
- 10 m length.

Product description

Range of standard flexible plastic duct for ventilation systems in individual houses. Available in different diameters from Ø 80 mm to Ø 200 mm. Practical packaging in 10 m net.

Fields of application

Individual residential housing, New, Refurbishment

Installation

- use a packing knife to cut ALGAINE to size,
- fully extend ALGAINE and limit bend effects when installing the ducts,
- use EasyClip connectors to ensure an airtight seal on connections to fan units and ventilation terminals.

Reference arguments

Application

- Flexible plastic ducts for exhaust and heat recovery ventilation systems in individual houses, new builds or refurbishment

Description

- Economical
- Easy to store and transport
- Craft knife required to cut
- Packaged in net

Main characteristics

- standard flexible plastic duct,
- diameters:
 - Ø 63 mm,
 - Ø 80 mm,
 - Ø 100 mm,
 - Ø 125 mm,
 - Ø 150 mm,
 - Ø 160 mm,
 - Ø 200 mm.
- material: PVC film + steel wire,
- packaging: 10 m net,
- temperature range: -10°C / +60°C.

General data

References	Maximum use temperature (°C)	Minimum use temperature (°C)
11091603	60	-10

11091603

Standard ALGAINE Ø 125 mm (10 m net)

Dimensional data

References	L (mm)	Ø (mm)	Weight (kg)
11091603	10000	125	0,93