11091600 Standard ALGAINE Ø 63 mm (10 m net)

Range of standard flexible plastic duct for ventilation systems in individual houses.



Standard Algaine

PRODUCT BENEFITS

• 10 m lengt

Product description

Range of standard flexible plastic duct for ventilation systems in individual houses. Available in different diameters from Ø 80 mm to Ø 200 mm. Practical packaging in 10 m net.

Fields of application

Individual residential housing, New, Refurbishment

Installation

- use a packing knife to cut ALGAINE to size,
- fully extend ALGAINE and limit bend effects when installing the ducts,
- use EasyClip connectors to ensure an airtight seal on connections to fan units and ventilation terminals.

Reference arguments

Application

- Algaine flexible plastic ducts for exhaust and heat recovery ventilation systems in individual housing
- new builds or refurbishment

Description

- Net 10 m standard Algaine diameter 63 mm
- PVC film + steel wire
- Temperature range: -10°C to +60°C
- 10 m net
- Markings every metre

Main characteristics

- standard flexible plastic duct,
- diameters:
- Ø 63 mm,
- Ø 80 mm,
- Ø 100 mm,
- Ø 125 mm,
- Ø 150 mm,
- Ø 160 mm,
- Ø 200 mm.
- material: PVC film + steel wire,
- packaging: 10 m net,
- temperature range: -10°C / +60°C.

General data

References	Maximum use temperature (°C)	Minimum use temperature (°C)
11091600	60	-10



11091600 Standard ALGAINE Ø 63 mm (10 m net)

Dimensional data

References	L (mm)	Ø (mm)	Weight (kg)
11091600	10000	63	0,85