

# 11024108

## TAHA® 400 M4

The roof fan range that makes ventilation easier.



Taha

### PRODUCT BENEFITS

- airflow from 500 to 4,000 m<sup>3</sup>/h,
- refined design,
- wide range of installation accessories,
- ErP-compliant with speed controller.

### REGLEMENTATIONS AND COMPLIANCES

Technical Opinion no.: 14.5/16-2185\_V2

### Principles of operation

Roof exhaust fan with horizontal discharge for CMEV in multi-occupancy housing and non-residential buildings.

### Product description

Aluminium housing for good corrosion resistance, vertical discharge.

### Fields of application

Multi-occupancy residential housing, New, Refurbishment, Non-residential buildings

### Installation

- horizontal air outlet,
- flat or sloping roof with masonry base or accessory.

### Reference arguments

Application:

- Roof exhaust fan for flat or sloping roof, horizontal jet, 4000 m<sup>3</sup>/h
- Designed for multi-occupancy residential or non-residential CMEV

Description:

- Aluminium unit for good corrosion resistance
- Anti-bird screen
- Backward curve centrifuge impeller
- Asynchronous motor single-phase IP54 - 4 poles

### Main characteristics

- 5 sizes available from 500 to 4000 m<sup>3</sup>/h: (for flowrates above 4000 m<sup>3</sup>/h see TAHA® Micro-Watt),
- made of weatherproof AlMg3 aluminium with a very low height. The motor unit tilts for easy installation (optional accessories) and maintenance,
- the air outlet features a protective screen against intrusion, birds, and other foreign objects,
- backward curve centrifuge impeller balanced on the motor according to quality class G 6.3 of DIN / ISO 1940,
- the drive motor is designed for maintenance-free operation, thanks to its ball bearings with lifetime lubrication,
- the motor is protected by a thermal switch integrated in the winding,
- single-phase power supply.

### Accessories

Désignations	References
Backdraft damper Ø 400	11024464
Proximity switch 1-speed 1-Ph - 0.9 kW	11056196
Connection flange D400	11024454
Flexible sleeve 400	11024459
INSULATED STACK BASE 355 INCLINED ROOF	11024252
Insulated flat roof base TAHA-TAVA 355	11024442
INSULATED BASE 355 SILENCER INCLINED ROOF	11024257
Insulated flat roof base with sound attenuator TAHA-TAVA 355	11024448


## 11024108 TAHA® 400 M4

### General data

References	Type of motor
11024108	AC

### Dimensional data

References	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	Weight (kg)
11024108	333	745	598	192,5	450	4 x Ø11	Ø438 M6x15 (6x)	19,5



Taha


### Airflow data

References	Airflow (m³/h)
11024108	3500

### Electrical datas

References	Protection rating	Max. current consumption SINGLE-PHASE 230 V (A)	Power supply	Number of poles	Max. power	Max. power
11024108	IP54	2.7	Single-phase	4	0,456	456

### Curve



Taha-400