

#### Connector



The TE 45° T-piece is used to connect two ductwork branches at an angle of 45°.



Té Oblique 45°

# **Product description**

The TE 45° T-piece is used to connect two ductwork branches at an angle of 45°. Use a TO instead of a TE for an air supply duct. It ensures leak-free installation without excessive pressure losses on the branch connection.

### **Fields of application**

Multi-occupancy residential housing, New, Refurbishment, Non-residential buildings

#### Installation

- easy assembly of interlocking accessories: ducts are female, accessories are male,
- Final seal requires sealant and/or perforated strip,
- attached to duct using self-tapping screws (4 to 6 depending on diameter).

# **Reference arguments**

Application:

- Connects two ducting branches at an angle of 45° on non-residential and multi-occupancy residential systems
- Especially efficient for air supply compared to a 90° T-piece


#### Description:

• Angled T-piece galvanised steel diameter 630/250 mm

# Main characteristics

- available in diameters from 80 to 900,
- galvanised steel as per EN 10346 ensuring uniformity of coating,
- M0 fire certification.

## **Dimensional data**



Dimensional drawing 45° Branch piece

# Connector

# 11093264 TO GALVA ANGLE T-PIECE D630/250

Regulatory data

References 11093264

Fire protection rating M0