

Axial heat and smoke exhaust fan

11017062

VAV CIRCULAR INSULATED XVA D400

The VAV enables precise airflow adjustment based on a signal whatever the pressure variation, to adapt the quantity of air to actual needs.



PRODUCT BENEFITS

- precise adjustment of airflow,
- easy to adjust on site,
- low leak rate (class C).

Principles of operation

According to a 0-10 V or 2-10 V external signal, the VAV will adjust the airflow over a wide range with precision thanks to its built-in pressure taps. Minimum and maximum airflow settings can be adjusted on site using the Belimo app or the associated configuration tool.

Product description

The VAV is an airflow controller which will adjust the airflow according to an external signal from a sensor, BMS, etc. Its integrated pressure sensors maintain the airflow specified by the signal whatever the pressure variations. The airflow is kept at the exact level required for greater comfort, IAQ and energy savings

Fields of application

New, Refurbishment, Non-residential buildings

Installation

- directly installed between two circular ducts,
- installed horizontally or vertically,
- airflow direction indicated on component,
- adjustment of min./max. airflow on site,
- 24V AC power supply.

Reference arguments

The VAV is an airflow controller which will adjust the airflow according to an external signal from a sensor, BMS, etc. Its integrated pressure sensors maintain the airflow specified by the signal whatever the pressure variations. The airflow is kept at the exact level required for greater comfort, IAQ and energy savings

Accessories

Description	Variants
Sens CO2 sensor	11017090
Inspection hatch D400 400 x 300	11091841

General data

Variants	Airflow accuracy	Insulation material
11017062	5% (> 2 m/s)	Mineral wool

Dimensional data

Variants	L (mm)	Ø (mm)	Ø external (mm)	Weight (kg)
11017062	650	400	500	17

Airflow data

Variants	Airflow range (m³/h)	Pressure range (Pa)
11017062	900-5425	50-1000

Electrical datas

Variants	Frequency (Hz)	Protection current (A)	Power consumption	Power supply	Voltage (V)
11017062	50/60	6	4.5	Single-phase	24

Axial heat and smoke exhaust fan

11017062

VAV CIRCULAR INSULATED XVA D400

Regulatory data

Variants	Fire protection rating
11017062	A1