

Axial heat and smoke exhaust fan

11017196
VAV CIRCULAR INSULATED XVA D400

The VAV enables precise airflow adjustment based on a signal whatever the pressure variation, to adapt the quantity of air to actual needs.



PRODUCT BENEFITS

- precise adjustment of airflow,
- easy to adjust on site,
- low leak rate (class C).

Principles of operation

According to a 0-10 V or 2-10 V external signal, the VAV will adjust the airflow over a wide range with precision thanks to its built-in pressure taps. Minimum and maximum airflow settings can be adjusted on site using the Belimo app or the associated configuration tool.

Product description

The VAV is an airflow controller which will adjust the airflow according to an external signal from a sensor, BMS, etc. Its integrated pressure sensors maintain the airflow specified by the signal whatever the pressure variations. The airflow is kept at the exact level required for greater comfort, IAQ and energy savings

Fields of application

New, Refurbishment, Non-residential buildings

Installation

- directly installed between two circular ducts,
- installed horizontally or vertically,
- airflow direction indicated on component,
- adjustment of min./max. airflow on site,
- 24V AC power supply.

Reference arguments

The VAV D400 is an airflow controller which adjusts the airflow according to an external signal from a sensor, BMS, etc. Its integrated pressure sensors maintain the airflow specified by the signal whatever the pressure variations. The airflow is kept at the exact level required for greater comfort, IAQ and energy savings

Dimensional data

Variants	L (mm)	Ø (mm)	Ø external (mm)	Weight (kg)
11017196	630	400	460	11.5

Airflow data

Variants	Airflow range (m³/h)
11017196	543-5430

Electrical datas

Variants	Voltage (V)	Protection current (A)	Power supply
11017196	24	IP54	Single-phase

Regulatory data

Variants	Fire protection rating
11017196	M1